

Xenomai Native skin API Reference Manual
2.3.5

Generated by Doxygen 1.5.3

Sun Dec 9 10:37:39 2007

Contents

1 Xenomai Native skin API Module Index	1
1.1 Xenomai Native skin API Modules	1
2 Xenomai Native skin API Data Structure Index	3
2.1 Xenomai Native skin API Data Structures	3
3 Xenomai Native skin API File Index	5
3.1 Xenomai Native skin API File List	5
4 Xenomai Native skin API Module Documentation	7
4.1 Task Status	7
4.2 Alarm services.	9
4.3 Condition variable services.	15
4.4 Event flag group services.	22
4.5 Memory heap services.	29
4.6 Interrupt management services.	36
4.7 Native Xenomai API.	45
4.8 Mutex services.	46
4.9 Message pipe services.	52
4.10 Message queue services.	63
4.11 Counting semaphore services.	74
4.12 Task management services.	81
4.13 Timer management services.	107
5 Xenomai Native skin API Data Structure Documentation	113
5.1 RT_TASK_INFO Struct Reference	113
5.2 RT_TASK_MCB Struct Reference	115
6 Xenomai Native skin API File Documentation	117
6.1 include/native/alarm.h File Reference	117

6.2	include/native/cond.h File Reference	119
6.3	include/native/event.h File Reference	120
6.4	include/native/heap.h File Reference	121
6.5	include/native/intr.h File Reference	122
6.6	include/native/misc.h File Reference	124
6.7	include/native/mutex.h File Reference	125
6.8	include/native/pipe.h File Reference	126
6.9	include/native/queue.h File Reference	127
6.10	include/native/sem.h File Reference	129
6.11	include/native/task.h File Reference	130
6.12	include/native/timer.h File Reference	133
6.13	include/native/types.h File Reference	135
6.14	ksrc/skins/native/module.c File Reference	136
6.15	ksrc/skins/native/syscall.c File Reference	137
6.16	ksrc/skins/native/alarm.c File Reference	138
6.17	ksrc/skins/native/cond.c File Reference	139
6.18	ksrc/skins/native/event.c File Reference	140
6.19	ksrc/skins/native/heap.c File Reference	141
6.20	ksrc/skins/native/intr.c File Reference	142
6.21	ksrc/skins/native/mutex.c File Reference	143
6.22	ksrc/skins/native/pipe.c File Reference	144
6.23	ksrc/skins/native/queue.c File Reference	145
6.24	ksrc/skins/native/sem.c File Reference	146
6.25	ksrc/skins/native/task.c File Reference	147
6.26	ksrc/skins/native/timer.c File Reference	149

Chapter 1

Xenomai Native skin API Module Index

1.1 Xenomai Native skin API Modules

Here is a list of all modules:

Native Xenomai API.	45
Task Status	7
Alarm services.	9
Condition variable services.	15
Event flag group services.	22
Memory heap services.	29
Interrupt management services.	36
Mutex services.	46
Message pipe services.	52
Message queue services.	63
Counting semaphore services.	74
Task management services.	81
Timer management services.	107

Chapter 2

Xenomai Native skin API Data Structure Index

2.1 Xenomai Native skin API Data Structures

Here are the data structures with brief descriptions:

RT_TASK_INFO (Structure containing task-information useful to users)	113
RT_TASK_MCB (Structure used in passing messages between tasks)	115

Chapter 3

Xenomai Native skin API File Index

3.1 Xenomai Native skin API File List

Here is a list of all documented files with brief descriptions:


include/native/alarm.h (This file is part of the Xenomai project)	117
include/native/cond.h (This file is part of the Xenomai project)	119
include/native/event.h (This file is part of the Xenomai project)	120
include/native/heap.h (This file is part of the Xenomai project)	121
include/native/intr.h (This file is part of the Xenomai project)	122
include/native/misc.h (This file is part of the Xenomai project)	124
include/native/mutex.h (This file is part of the Xenomai project)	125
include/native/pipe.h (This file is part of the Xenomai project)	126
include/native/queue.h (This file is part of the Xenomai project)	127
include/native/sem.h (This file is part of the Xenomai project)	129
include/native/syscall.h	??
include/native/task.h (This file is part of the Xenomai project)	130
include/native/timer.h (This file is part of the Xenomai project)	133
include/native/types.h (This file is part of the Xenomai project)	135
ksrc/skins/native/alarm.c (This file is part of the Xenomai project)	138
ksrc/skins/native/cond.c (This file is part of the Xenomai project)	139
ksrc/skins/native/event.c (This file is part of the Xenomai project)	140
ksrc/skins/native/heap.c (This file is part of the Xenomai project)	141
ksrc/skins/native/intr.c (This file is part of the Xenomai project)	142
ksrc/skins/native/module.c (This file is part of the Xenomai project)	136
ksrc/skins/native/mutex.c (This file is part of the Xenomai project)	143
ksrc/skins/native/pipe.c (This file is part of the Xenomai project)	144
ksrc/skins/native/queue.c (This file is part of the Xenomai project)	145
ksrc/skins/native/sem.c (This file is part of the Xenomai project)	146
ksrc/skins/native/syscall.c (This file is part of the Xenomai project)	137
ksrc/skins/native/task.c (This file is part of the Xenomai project)	147
ksrc/skins/native/timer.c (This file is part of the Xenomai project)	149

Chapter 4

Xenomai Native skin API Module Documentation

4.1 Task Status

Collaboration diagram for Task Status:



4.1.1 Detailed Description

Defines used to specify task state and/or mode.

Defines

- #define `T_BLOCKED` XNPEND
See XNPEND.
- #define `T_DELAYED` XNDELAY
See XNDELAY.
- #define `T_READY` XNREADY
See XNREADY.
- #define `T_DORMANT` XNDORMANT
See XNDORMANT.
- #define `T_STARTED` XNSTARTED
See XNSTARTED.
- #define `T_BOOST` XNBOOST
See XNBOOST.

- #define [T_LOCK](#) XNLOCK
See XNLOCK.
- #define [T_RRB](#) XNRRB
See XNRRB.
- #define [T_NOSIG](#) XNASDI
See XNASDI.
- #define [T_SHIELD](#) XNSHIELD
See XNSHIELD.
- #define [T_WARNSW](#) XNTRAPSW
See XNTRAPSW.
- #define [T_RPIOFF](#) XNRPIOFF
See XNRPIOFF.

4.2 Alarm services.

Collaboration diagram for Alarm services.:



4.2.1 Detailed Description

Alarms are general watchdog timers. Any Xenomai task may create any number of alarms and use them to run a user-defined handler, after a specified initial delay has elapsed. Alarms can be either one shot or periodic; in the latter case, the real-time kernel automatically reprograms the alarm for the next shot according to a user-defined interval value.

Files

- file [alarm.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_alarm_create](#) (RT_ALARM *alarm, const char *name, rt_alarm_t handler, void *cookie)
- int [rt_alarm_delete](#) (RT_ALARM *alarm)
- int [rt_alarm_start](#) (RT_ALARM *alarm, RTIME value, RTIME interval)
- int [rt_alarm_stop](#) (RT_ALARM *alarm)
- int [rt_alarm_inquire](#) (RT_ALARM *alarm, RT_ALARM_INFO *info)
- int [rt_alarm_create](#) (RT_ALARM *alarm, const char *name)
- int [rt_alarm_wait](#) (RT_ALARM *alarm)

4.2.2 Function Documentation

4.2.2.1 int [rt_alarm_create](#) (RT_ALARM * alarm, const char * name)

Create an alarm object from user-space.

Initializes an alarm object from a user-space application. Alarms can be made periodic or oneshot, depending on the reload interval value passed to [rt_alarm_start\(\)](#) for them. In this mode, the basic principle is to define some alarm server task which routinely waits for the next incoming alarm event through the [rt_alarm_wait\(\)](#) syscall.

Parameters:

alarm The address of an alarm descriptor Xenomai will use to store the alarm-related data. This descriptor must always be valid while the alarm is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the alarm. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created alarm.

Returns:

0 is returned upon success. Otherwise:

- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the alarm.
- -EEXIST is returned if the *name* is already in use by some registered object.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- User-space task

Rescheduling: possible.

Note:

It is possible to combine kernel-based alarm handling with waiter threads pending on the same alarm object from user-space through the `rt_alarm_wait()` service. For this purpose, the `rt_alarm_handler()` routine which is internally invoked to wake up alarm servers in user-space is accessible to user-provided alarm handlers in kernel space, and should be called from there in order to unblock any thread sleeping on the `rt_alarm_wait()` service.

4.2.2.2 `int rt_alarm_create (RT_ALARM * alarm, const char * name, rt_alarm_t handler, void * cookie)`

Create an alarm object from kernel space.

Create an object triggering an alarm routine at a specified time in the future. Alarms can be made periodic or oneshot, depending on the reload interval value passed to `rt_alarm_start()` for them. In kernel space, alarms are immediately notified on behalf of the timer interrupt to a user-defined handler.

Parameters:

alarm The address of an alarm descriptor Xenomai will use to store the alarm-related data. This descriptor must always be valid while the alarm is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the alarm. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created alarm.

handler The address of the routine to call when the alarm expires. This routine will be passed the address of the current alarm descriptor, and the opaque *cookie*.

cookie A user-defined opaque cookie the real-time kernel will pass to the alarm handler as its second argument.

Returns:

0 is returned upon success. Otherwise:

- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the alarm.
- -EEXIST is returned if the *name* is already in use by some registered object.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task

Rescheduling: possible.

Note:

It is possible to combine kernel-based alarm handling with waiter threads pending on the same alarm object from user-space through the [rt_alarm_wait\(\)](#) service. For this purpose, the [rt_alarm_handler\(\)](#) routine which is internally invoked to wake up alarm servers in user-space is accessible to user-provided alarm handlers in kernel space, and should be called from there in order to unblock any thread sleeping on the [rt_alarm_wait\(\)](#) service.

4.2.2.3 `int rt_alarm_delete (RT_ALARM * alarm)`

Delete an alarm.

Destroy an alarm. An alarm exists in the system since [rt_alarm_create\(\)](#) has been called to create it, so this service must be called in order to destroy it afterwards.

Parameters:

alarm The descriptor address of the affected alarm.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *alarm* is not a alarm descriptor.
- -EIDRM is returned if *alarm* is a deleted alarm descriptor.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: never.

4.2.2.4 `int rt_alarm_inquire (RT_ALARM * alarm, RT_ALARM_INFO * info)`

Inquire about an alarm.

Return various information about the status of a given alarm.

Parameters:

alarm The descriptor address of the inquired alarm.

info The address of a structure the alarm information will be written to.

The expiration date returned in the information block is converted to the current time unit. The special value `TM_INFINITE` is returned if *alarm* is currently inactive/stopped. In single-shot mode, it might happen that the alarm has already expired when this service is run (even if the associated handler has not been fired yet); in such a case, 1 is returned.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success. Otherwise:

- `-EINVAL` is returned if *alarm* is not a alarm descriptor.
- `-EIDRM` is returned if *alarm* is a deleted alarm descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.2.2.5 `int rt_alarm_start (RT_ALARM * alarm, RTIME value, RTIME interval)`

Start an alarm.

Program the trigger date of an alarm object. An alarm can be either periodic or oneshot, depending on the reload value passed to this routine. The given alarm must have been previously created by a call to `rt_alarm_create()`.

Alarm handlers are always called on behalf of Xenomai's internal timer tick handler, so the Xenomai services which can be called from such handlers are restricted to the set of services available on behalf of any ISR.

This service overrides any previous setup of the expiry date and reload interval for the given alarm.

Parameters:

alarm The descriptor address of the affected alarm.

value The relative date of the initial alarm shot, expressed in clock ticks (see note).

interval The reload value of the alarm. It is a periodic interval value to be used for reprogramming the next alarm shot, expressed in clock ticks (see note). If *interval* is equal to `TM_INFINITE`, the alarm will not be reloaded after it has expired.

Returns:

0 is returned upon success. Otherwise:

- `-EINVAL` is returned if *alarm* is not a alarm descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.2.2.6 `int rt_alarm_stop (RT_ALARM * alarm)`

Stop an alarm.

Disarm an alarm object previously armed using `rt_alarm_start()` so that it will not trigger until is re-armed.

Parameters:

alarm The descriptor address of the released alarm.

Returns:

0 is returned upon success. Otherwise:

- `-EINVAL` is returned if *alarm* is not a alarm descriptor.
- `-EIDRM` is returned if *alarm* is a deleted alarm descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code

- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.2.2.7 `int rt_alarm_wait (RT_ALARM * alarm)`

Wait for the next alarm shot.

This user-space only call allows the current task to suspend execution until the specified alarm triggers. The priority of the current task is raised above all other Xenomai tasks - except those also undergoing an alarm or interrupt wait (see [rt_intr_wait\(\)](#)) - so that it would preempt any of them under normal circumstances (i.e. no scheduler lock).

Parameters:

alarm The descriptor address of the awaited alarm.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *alarm* is not an alarm descriptor.
- -EPERM is returned if this service was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).
- -EIDRM is returned if *alarm* is a deleted alarm descriptor, including if the deletion occurred while the caller was waiting for its next shot.
- -EINTR is returned if [rt_task_unblock\(\)](#) has been called for the current task before the next alarm shot.

Environments:

This service can be called from:

- User-space task

Rescheduling: always.

4.3 Condition variable services.

Collaboration diagram for Condition variable services.:



4.3.1 Detailed Description

Condition variable services.

A condition variable is a synchronization object which allows tasks to suspend execution until some predicate on shared data is satisfied. The basic operations on conditions are: signal the condition (when the predicate becomes true), and wait for the condition, blocking the task execution until another task signals the condition. A condition variable must always be associated with a mutex, to avoid a well-known race condition where a task prepares to wait on a condition variable and another task signals the condition just before the first task actually waits on it.

Files

- file [cond.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_cond_create](#) (RT_COND *cond, const char *name)
- int [rt_cond_delete](#) (RT_COND *cond)
- int [rt_cond_signal](#) (RT_COND *cond)
- int [rt_cond_broadcast](#) (RT_COND *cond)
- int [rt_cond_wait](#) (RT_COND *cond, RT_MUTEX *mutex, RTIME timeout)
- int [rt_cond_inquire](#) (RT_COND *cond, RT_COND_INFO *info)
- int [rt_cond_bind](#) (RT_COND *cond, const char *name, RTIME timeout)
- static int [rt_cond_unbind](#) (RT_COND *cond)

4.3.2 Function Documentation

4.3.2.1 int [rt_cond_bind](#) (RT_COND * cond, const char * name, RTIME timeout)

Bind to a condition variable.

This user-space only service retrieves the uniform descriptor of a given Xenomai condition variable identified by its symbolic name. If the condition variable does not exist on entry, this service blocks the caller until a condition variable of the given name is created.

Parameters:

name A valid NULL-terminated name which identifies the condition variable to bind to.

cond The address of a condition variable descriptor retrieved by the operation. Contents of this memory is undefined upon failure.

timeout The number of clock ticks to wait for the registration to occur (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until the object is registered. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if the object is not registered on entry.

Returns:

0 is returned upon success. Otherwise:

- `-EFAULT` is returned if *cond* or *name* is referencing invalid memory.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before the retrieval has completed.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and the searched object is not registered on entry.
- `-ETIMEDOUT` is returned if the object cannot be retrieved within the specified amount of time.
- `-EPERM` is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.3.2.2 `int rt_cond_broadcast (RT_COND * cond)`

Broadcast a condition variable.

If the condition variable is pended, all tasks currently waiting on it are immediately unblocked.

Parameters:

cond The descriptor address of the affected condition variable.

Returns:

0 is returned upon success. Otherwise:

- `-EINVAL` is returned if *cond* is not a condition variable descriptor.

- -EIDRM is returned if *cond* is a deleted condition variable descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.3.2.3 `int rt_cond_create (RT_COND * cond, const char * name)`

Create a condition variable.

Create a synchronization object that allows tasks to suspend execution until some predicate on shared data is satisfied.

Parameters:

cond The address of a condition variable descriptor Xenomai will use to store the variable-related data. This descriptor must always be valid while the variable is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the condition variable. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created variable.

Returns:

0 is returned upon success. Otherwise:

- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the condition variable.
- -EEXIST is returned if the *name* is already in use by some registered object.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.3.2.4 `int rt_cond_delete (RT_COND * cond)`

Delete a condition variable.

Destroy a condition variable and release all the tasks currently pending on it. A condition variable exists in the system since `rt_cond_create()` has been called to create it, so this service must be called in order to destroy it afterwards.

Parameters:

cond The descriptor address of the affected condition variable.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *cond* is not a condition variable descriptor.
- -EIDRM is returned if *cond* is a deleted condition variable descriptor.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.3.2.5 `int rt_cond_inquire (RT_COND * cond, RT_COND_INFO * info)`

Inquire about a condition variable.

Return various information about the status of a given condition variable.

Parameters:

cond The descriptor address of the inquired condition variable.

info The address of a structure the condition variable information will be written to.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success. Otherwise:

- -EINVAL is returned if *cond* is not a condition variable descriptor.
- -EIDRM is returned if *cond* is a deleted condition variable descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.3.2.6 `int rt_cond_signal (RT_COND * cond)`

Signal a condition variable.

If the condition variable is pended, the first waiting task (by queuing priority order) is immediately unblocked.

Parameters:

cond The descriptor address of the affected condition variable.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *cond* is not a condition variable descriptor.
- -EIDRM is returned if *cond* is a deleted condition variable descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.3.2.7 `int rt_cond_unbind (RT_COND * cond) [inline, static]`

Unbind from a condition variable.

This user-space only service unbinds the calling task from the condition variable object previously retrieved by a call to [rt_cond_bind\(\)](#).

Parameters:

cond The address of a condition variable descriptor to unbind from.

Returns:

0 is always returned.

This service can be called from:

- User-space task.

Rescheduling: never.

4.3.2.8 int rt_cond_wait (RT_COND * cond, RT_MUTEX * mutex, RTIME timeout)

Wait on a condition.

This service atomically release the mutex and causes the calling task to block on the specified condition variable. The caller will be unblocked when the variable is signaled, and the mutex re-acquired before returning from this service.

Tasks pend on condition variables by priority order.

Parameters:

cond The descriptor address of the affected condition variable.

mutex The descriptor address of the mutex protecting the condition variable.

timeout The number of clock ticks to wait for the condition variable to be signaled (see note).
Passing TM_INFINITE causes the caller to block indefinitely until the condition variable is signaled.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *mutex* is not a mutex descriptor, or *cond* is not a condition variable descriptor.
- -EIDRM is returned if *mutex* or *cond* is a deleted object descriptor, including if the deletion occurred while the caller was sleeping on the variable.
- -EINTR is returned if [rt_task_unblock\(\)](#) has been called for the waiting task before the condition variable has been signaled.
- -EWOULDBLOCK is returned if *timeout* equals TM_NONBLOCK.

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.4 Event flag group services.

Collaboration diagram for Event flag group services.:



4.4.1 Detailed Description

An event flag group is a synchronization object represented by a long-word structure; every available bit in such word can be used to map a user-defined event flag. When a flag is set, the associated event is said to have occurred. Xenomai tasks and interrupt handlers can use event flags to signal the occurrence of events to other tasks; those tasks can either wait for the events to occur in a conjunctive manner (all awaited events must have occurred to wake up), or in a disjunctive way (at least one of the awaited events must have occurred to wake up).

Files

- file [event.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_event_create](#) (RT_EVENT *event, const char *name, unsigned long ival, int mode)
- int [rt_event_delete](#) (RT_EVENT *event)
- int [rt_event_signal](#) (RT_EVENT *event, unsigned long mask)
- int [rt_event_wait](#) (RT_EVENT *event, unsigned long mask, unsigned long *mask_r, int mode, RTIME timeout)
- int [rt_event_clear](#) (RT_EVENT *event, unsigned long mask, unsigned long *mask_r)
- int [rt_event_inquire](#) (RT_EVENT *event, RT_EVENT_INFO *info)
- int [rt_event_bind](#) (RT_EVENT *event, const char *name, RTIME timeout)
- static int [rt_event_unbind](#) (RT_EVENT *event)

4.4.2 Function Documentation

4.4.2.1 int [rt_event_bind](#) (RT_EVENT * event, const char * name, RTIME timeout)

Bind to an event flag group.

This user-space only service retrieves the uniform descriptor of a given Xenomai event flag group identified by its symbolic name. If the event flag group does not exist on entry, this service blocks the caller until an event flag group of the given name is created.

Parameters:

name A valid NULL-terminated name which identifies the event flag group to bind to.

event The address of an event flag group descriptor retrieved by the operation. Contents of this memory is undefined upon failure.

timeout The number of clock ticks to wait for the registration to occur (see note). Passing TM_INFINITE causes the caller to block indefinitely until the object is registered. Passing TM_NONBLOCK causes the service to return immediately without waiting if the object is not registered on entry.

Returns:

0 is returned upon success. Otherwise:

- -EFAULT is returned if *event* or *name* is referencing invalid memory.
- -EINTR is returned if `rt_task_unblock()` has been called for the waiting task before the retrieval has completed.
- -EWOULDBLOCK is returned if *timeout* is equal to TM_NONBLOCK and the searched object is not registered on entry.
- -ETIMEDOUT is returned if the object cannot be retrieved within the specified amount of time.
- -EPERM is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.4.2.2 int rt_event_clear (RT_EVENT * event, unsigned long mask, unsigned long * mask_r)

Clear an event group.

Clears a set of flags from an event mask.

Parameters:

event The descriptor address of the affected event.

mask The set of events to be cleared.

mask_r If non-NULL, *mask_r* is the address of a memory location which will be written upon success with the previous value of the event group before the flags are cleared.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *event* is not an event group descriptor.
- -EIDRM is returned if *event* is a deleted event group descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.4.2.3 `int rt_event_create (RT_EVENT * event, const char * name, unsigned long ivalue, int mode)`

Create an event group.

Event groups provide for task synchronization by allowing a set of flags (or "events") to be waited for and posted atomically. An event group contains a mask of received events; any set of bits from the event mask can be pended or posted in a single operation.

Tasks can wait for a conjunctive (AND) or disjunctive (OR) set of events to occur. A task pending on an event group in conjunctive mode is woken up as soon as all awaited events are set in the event mask. A task pending on an event group in disjunctive mode is woken up as soon as any awaited event is set in the event mask.

Parameters:

event The address of an event group descriptor Xenomai will use to store the event-related data. This descriptor must always be valid while the group is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the group. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created event group.

ivalue The initial value of the group's event mask.

mode The event group creation mode. The following flags can be OR'ed into this bitmask, each of them affecting the new group:

- EV_FIFO makes tasks pend in FIFO order on the event group.
- EV_PRIO makes tasks pend in priority order on the event group.

Returns:

0 is returned upon success. Otherwise:

- -EEXIST is returned if the *name* is already in use by some registered object.
- -EPERM is returned if this service was called from an asynchronous context.
- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the event group.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.4.2.4 `int rt_event_delete (RT_EVENT * event)`

Delete an event group.

Destroy an event group and release all the tasks currently pending on it. An event group exists in the system since `rt_event_create()` has been called to create it, so this service must be called in order to destroy it afterwards.

Parameters:

event The descriptor address of the affected event group.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *event* is not a event group descriptor.
- -EIDRM is returned if *event* is a deleted event group descriptor.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.4.2.5 `int rt_event_inquire (RT_EVENT * event, RT_EVENT_INFO * info)`

Inquire about an event group.

Return various information about the status of a specified event group.

Parameters:

event The descriptor address of the inquired event group.

info The address of a structure the event group information will be written to.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success. Otherwise:

- -EINVAL is returned if *event* is not a event group descriptor.
- -EIDRM is returned if *event* is a deleted event group descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.4.2.6 `int rt_event_signal (RT_EVENT * event, unsigned long mask)`

Post an event group.

Post a set of bits to the event mask. All tasks having their wait request fulfilled by the posted events are resumed.

Parameters:

event The descriptor address of the affected event.

mask The set of events to be posted.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *event* is not an event group descriptor.
- -EIDRM is returned if *event* is a deleted event group descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.4.2.7 `int rt_event_unbind (RT_EVENT * event) [inline, static]`

Unbind from an event flag group.

This user-space only service unbinds the calling task from the event flag group object previously retrieved by a call to `rt_event_bind()`.

Parameters:

event The address of an event flag group descriptor to unbind from.

Returns:

0 is always returned.

This service can be called from:

- User-space task.

Rescheduling: never.

4.4.2.8 `int rt_event_wait (RT_EVENT * event, unsigned long mask, unsigned long * mask_r, int mode, RTIME timeout)`

Pend on an event group.

Waits for one or more events on the specified event group, either in conjunctive or disjunctive mode.

If the specified set of bits is not set, the calling task is blocked. The task is not resumed until the request is fulfilled. The event bits are NOT cleared from the event group when a request is satisfied; `rt_event_wait()` will return immediately with success for the same event mask until `rt_event_clear()` is called to clear those bits.

Parameters:

event The descriptor address of the affected event group.

mask The set of bits to wait for. Passing zero causes this service to return immediately with a success value; the current value of the event mask is also copied to *mask_r*.

mask_r The value of the event mask at the time the task was readied.

mode The pend mode. The following flags can be OR'ed into this bitmask, each of them affecting the operation:

- `EV_ANY` makes the task pend in disjunctive mode (i.e. OR); this means that the request is fulfilled when at least one bit set into *mask* is set in the current event mask.
- `EV_ALL` makes the task pend in conjunctive mode (i.e. AND); this means that the request is fulfilled when at all bits set into *mask* are set in the current event mask.

Parameters:

timeout The number of clock ticks to wait for fulfilling the request (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until the request is fulfilled. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if the request cannot be satisfied immediately.

Returns:

0 is returned upon success. Otherwise:

- `-EINVAL` is returned if *event* is not a event group descriptor.
- `-EIDRM` is returned if *event* is a deleted event group descriptor, including if the deletion occurred while the caller was sleeping on it before the request has been satisfied.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and the current event mask value does not satisfy the request.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before the request has been satisfied.
- `-ETIMEDOUT` is returned if the request has not been satisfied within the specified amount of time.
- `-EPERM` is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code or Interrupt service routine only if *timeout* is equal to `TM_NONBLOCK`.
- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.5 Memory heap services.

Collaboration diagram for Memory heap services.:



4.5.1 Detailed Description

Memory heaps are regions of memory used for dynamic memory allocation in a time-bounded fashion. Blocks of memory are allocated and freed in an arbitrary order and the pattern of allocation and size of blocks is not known until run time.

The implementation of the memory allocator follows the algorithm described in a USENIX 1988 paper called "Design of a General Purpose Memory Allocator for the 4.3BSD Unix Kernel" by Marshall K. McKusick and Michael J. Karels.

Xenomai memory heaps are built over the nucleus's heap objects, which in turn provide the needed support for sharing a memory area between kernel and user-space using direct memory mapping.

Files

- file [heap.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_heap_create](#) (RT_HEAP *heap, const char *name, size_t heapsize, int mode)

Create a memory heap or a shared memory segment.

- int [rt_heap_delete](#) (RT_HEAP *heap)
- int [rt_heap_alloc](#) (RT_HEAP *heap, size_t size, RTIME timeout, void **blockp)
- int [rt_heap_free](#) (RT_HEAP *heap, void *block)
- int [rt_heap_inquire](#) (RT_HEAP *heap, RT_HEAP_INFO *info)
- int [rt_heap_bind](#) (RT_HEAP *heap, const char *name, RTIME timeout)
- int [rt_heap_unbind](#) (RT_HEAP *heap)

4.5.2 Function Documentation

4.5.2.1 int [rt_heap_alloc](#) (RT_HEAP * heap, size_t size, RTIME timeout, void ** blockp)

Allocate a block or return the single segment base.

This service allocates a block from the heap's internal pool, or returns the address of the single memory segment in the caller's address space. Tasks may wait for some requested amount of memory to become available from local heaps.

Parameters:

heap The descriptor address of the heap to allocate a block from.

size The requested size in bytes of the block. If the heap is managed as a single-block area (H_SINGLE), this value can be either zero, or the same value given to [rt_heap_create\(\)](#). In that case, the same block covering the entire heap space will always be returned to all callers of this service.

timeout The number of clock ticks to wait for a block of sufficient size to be available from a local heap (see note). Passing TM_INFINITE causes the caller to block indefinitely until some block is eventually available. Passing TM_NONBLOCK causes the service to return immediately without waiting if no block is available on entry. This parameter has no influence if the heap is managed as a single-block area since the entire heap space is always available.

blockp A pointer to a memory location which will be written upon success with the address of the allocated block, or the start address of the single memory segment. In the former case, the block should be freed using [rt_heap_free\(\)](#).

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *heap* is not a heap descriptor, or *heap* is managed as a single-block area (i.e. H_SINGLE mode) and *size* is non-zero but does not match the original heap size passed to [rt_heap_create\(\)](#).
- -EIDRM is returned if *heap* is a deleted heap descriptor.
- -ETIMEDOUT is returned if *timeout* is different from TM_NONBLOCK and no block is available within the specified amount of time.
- -EWOULDBLOCK is returned if *timeout* is equal to TM_NONBLOCK and no block is immediately available on entry.
- -EINTR is returned if [rt_task_unblock\(\)](#) has been called for the waiting task before any block was available.
- -EPERM is returned if this service should block but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *timeout* is equal to TM_NONBLOCK, or the heap is managed as a single-block area.
- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation. Operations on single-block heaps never start the rescheduling procedure.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.5.2.2 int rt_heap_bind (RT_HEAP * heap, const char * name, RTIME timeout)

Bind to a mappable heap.

This user-space only service retrieves the uniform descriptor of a given mappable Xenomai heap identified by its symbolic name. If the heap does not exist on entry, this service blocks the caller until a heap of the given name is created.

Parameters:

name A valid NULL-terminated name which identifies the heap to bind to.

heap The address of a heap descriptor retrieved by the operation. Contents of this memory is undefined upon failure.

timeout The number of clock ticks to wait for the registration to occur (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until the object is registered. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if the object is not registered on entry.

Returns:

0 is returned upon success. Otherwise:

- `-EFAULT` is returned if *heap* or *name* is referencing invalid memory.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before the retrieval has completed.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and the searched object is not registered on entry.
- `-ETIMEDOUT` is returned if the object cannot be retrieved within the specified amount of time.
- `-EPERM` is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).
- `-ENOENT` is returned if the special file `/dev/rtheap` (character-mode, major 10, minor 254) is not available from the filesystem. This device is needed to map the shared heap memory into the caller's address space. udev-based systems should not need manual creation of such device entry. Environments:

This service can be called from:

- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.5.2.3 `int rt_heap_create (RT_HEAP * heap, const char * name, size_t heapsize, int mode)`

Create a memory heap or a shared memory segment.

Initializes a memory heap suitable for time-bounded allocation requests of dynamic memory. Memory heaps can be local to the kernel address space, or mapped to user-space.

In their simplest form, heaps are only accessible from kernel space, and are merely usable as regular memory allocators.

Heaps existing in kernel space can be mapped by user-space processes to their own address space provided `H_MAPPABLE` has been passed into the *mode* parameter.

By default, heaps support allocation of multiple blocks of memory in an arbitrary order. However, it is possible to ask for single-block management by passing the `H_SINGLE` flag into the *mode* parameter, in which case the entire memory space managed by the heap is made available as a unique block. In this mode, all allocation requests made through `rt_heap_alloc()` will then return the same block address, pointing at the beginning of the heap memory.

`H_SHARED` is a shorthand for creating shared memory segments transparently accessible from kernel and user-space contexts, which are basically single-block, mappable heaps. By proper use of a common *name*, all tasks can bind themselves to the same heap and thus share the same memory space, which start address should be subsequently retrieved by a call to `rt_heap_alloc()`.

Parameters:

heap The address of a heap descriptor Xenomai will use to store the heap-related data. This descriptor must always be valid while the heap is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the heap. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created heap. Mappable heaps must be given a valid name.

heapsize The size (in bytes) of the block pool which is going to be pre-allocated to the heap. Memory blocks will be claimed and released to this pool. The block pool is not extensible, so this value must be compatible with the highest memory pressure that could be expected.

mode The heap creation mode. The following flags can be OR'ed into this bitmask, each of them affecting the new heap:

- `H_FIFO` makes tasks pend in FIFO order on the heap when waiting for available blocks.
- `H_PRIO` makes tasks pend in priority order on the heap when waiting for available blocks.

- `H_MAPPABLE` causes the heap to be sharable between kernel and user-space contexts. Otherwise, the new heap is only available for kernel-based usage. This flag is implicitly set when the caller is running in user-space. This feature requires the real-time support in user-space to be configured in (`CONFIG_XENO_OPT_PERVASIVE`).
- `H_SINGLE` causes the entire heap space to be managed as a single memory block.
- `H_SHARED` is a shorthand for `H_MAPPABLE|H_SINGLE`, creating a global shared memory segment accessible from both the kernel and user-space contexts.
- `H_DMA` causes the block pool associated to the heap to be allocated in physically contiguous memory, suitable for DMA operations with I/O devices. A 128Kb limit exists for *heapsize* when this flag is passed.

Returns:

0 is returned upon success. Otherwise:

- `-EEXIST` is returned if the *name* is already in use by some registered object.
- `-EINVAL` is returned if *heapsize* is null, greater than the system limit, or *name* is null or empty for a mappable heap.
- `-ENOMEM` is returned if not enough system memory is available to create or register the heap. Additionally, and if `H_MAPPABLE` has been passed in *mode*, errors while mapping the block pool in the caller's address space might beget this return code too.
- `-EPERM` is returned if this service was called from an invalid context.
- `-ENOSYS` is returned if *mode* specifies `H_MAPPABLE`, but the real-time support in user-space is unavailable.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- User-space task (switches to secondary mode)

Rescheduling: possible.

4.5.2.4 int rt_heap_delete (RT_HEAP * heap)

Delete a real-time heap.

Destroy a heap and release all the tasks currently pending on it. A heap exists in the system since [rt_heap_create\(\)](#) has been called to create it, so this service must be called in order to destroy it afterwards.

Parameters:

heap The descriptor address of the affected heap.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *heap* is not a heap descriptor.
- -EIDRM is returned if *heap* is a deleted heap descriptor.
- -EPERM is returned if this service was called from an invalid context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- User-space task (switches to secondary mode).

Rescheduling: possible.

4.5.2.5 int rt_heap_free (RT_HEAP * heap, void * block)

Free a block.

This service releases a block to the heap's internal pool. If some task is currently waiting for a block so that it's pending request could be satisfied as a result of the release, it is immediately resumed.

If the heap is defined as a single-block area (i.e. H_SINGLE mode), this service leads to a null-effect and always returns successfully.

Parameters:

heap The address of the heap descriptor to which the block *block* belong.

block The address of the block to free.

Returns:

0 is returned upon success, or -EINVAL if *block* is not a valid block previously allocated by the [rt_heap_alloc\(\)](#) service.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.5.2.6 `int rt_heap_inquire (RT_HEAP * heap, RT_HEAP_INFO * info)`

Inquire about a heap.

Return various information about the status of a given heap.

Parameters:

heap The descriptor address of the inquired heap.

info The address of a structure the heap information will be written to.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success.
Otherwise:

- -EINVAL is returned if *heap* is not a message queue descriptor.
- -EIDRM is returned if *heap* is a deleted queue descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.5.2.7 `int rt_heap_unbind (RT_HEAP * heap)`

Unbind from a mappable heap.

This user-space only service unbinds the calling task from the heap object previously retrieved by a call to `rt_heap_bind()`.

Unbinding from a heap when it is no more needed is especially important in order to properly release the mapping resources used to attach the heap memory to the caller's address space.

Parameters:

heap The address of a heap descriptor to unbind from.

Returns:

0 is always returned.

This service can be called from:

- User-space task.

Rescheduling: never.

4.6 Interrupt management services.

Collaboration diagram for Interrupt management services.:



Files

- file [intr.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_intr_create](#) (RT_INTR *intr, const char *name, unsigned irq, rt_isr_t isr, rt_iack_t iack, int mode)
Create an interrupt object from kernel space.
- int [rt_intr_delete](#) (RT_INTR *intr)
- int [rt_intr_enable](#) (RT_INTR *intr)
Enable an interrupt object.
- int [rt_intr_disable](#) (RT_INTR *intr)
Disable an interrupt object.
- int [rt_intr_inquire](#) (RT_INTR *intr, RT_INTR_INFO *info)
- int [rt_intr_create](#) (RT_INTR *intr, const char *name, unsigned irq, int mode)
Create an interrupt object from user-space.
- int [rt_intr_wait](#) (RT_INTR *intr, RTIME timeout)
- int [rt_intr_bind](#) (RT_INTR *intr, const char *name, RTIME timeout)
- static int [rt_intr_unbind](#) (RT_INTR *intr)

4.6.1 Function Documentation

4.6.1.1 int [rt_intr_bind](#) (RT_INTR * intr, const char * name, RTIME timeout)

Bind to an interrupt object.

This user-space only service retrieves the uniform descriptor of a given Xenomai interrupt object identified by its IRQ number. If the object does not exist on entry, this service blocks the caller until an interrupt object of the given number is created. An interrupt is registered whenever a kernel-space task invokes the [rt_intr_create\(\)](#) service successfully for the given IRQ line.

Parameters:

- intr* The address of an interrupt object descriptor retrieved by the operation. Contents of this memory is undefined upon failure.
- name* An ASCII string standing for the symbolic name of the interrupt object to search for.

timeout The number of clock ticks to wait for the registration to occur (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until the object is registered. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if the object is not registered on entry.

Returns:

0 is returned upon success. Otherwise:

- `-EFAULT` is returned if *intr* is referencing invalid memory.
- `-EINVAL` is returned if *irq* is invalid.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before the retrieval has completed.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and the searched object is not registered on entry.
- `-ETIMEDOUT` is returned if the object cannot be retrieved within the specified amount of time.
- `-EPERM` is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.6.1.2 `int rt_intr_create (RT_INTR * intr, const char * name, unsigned irq, int mode)`

Create an interrupt object from user-space.

Initializes and associates an interrupt object with an IRQ line from a user-space application. In this mode, the basic principle is to define some interrupt server task which routinely waits for the next incoming IRQ event through the `rt_intr_wait()` syscall.

When an interrupt occurs on the given *irq* line, any task pending on the interrupt object through `rt_intr_wait()` is immediately awoken in order to deal with the hardware event. The interrupt service code may then call any Xenomai service available from user-space.

Parameters:

- intr* The address of a interrupt object descriptor Xenomai will use to store the object-specific data. This descriptor must always be valid while the object is active therefore it must be allocated in permanent memory.
- name* An ASCII string standing for the symbolic name of the interrupt object. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created interrupt objects.
- irq* The hardware interrupt channel associated with the interrupt object. This value is architecture-dependent.
- mode* The interrupt object creation mode. The following flags can be OR'ed into this bitmask:
- `I_NOAUTOENA` asks Xenomai not to re-enable the IRQ line before awakening the interrupt server task. This flag is functionally equivalent as always returning `RT_INTR_NOENABLE` from a kernel space interrupt handler.
 - `I_PROPAGATE` asks Xenomai to propagate the IRQ down the pipeline; in other words, the interrupt occurrence is chained to Linux after it has been processed by the Xenomai task. This flag is functionally equivalent as always returning `RT_INTR_PROPAGATE` from a kernel space interrupt handler.

Returns:

0 is returned upon success. Otherwise:

- `-ENOMEM` is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the interrupt object.
- `-EBUSY` is returned if the interrupt line is already in use by another interrupt object. Only a single interrupt object can be associated to any given interrupt line using `rt_intr_create()` at any time, regardless of the caller's execution space (kernel or user).

Environments:

This service can be called from:

- User-space task

Rescheduling: possible.

Note:

The interrupt source associated to the interrupt descriptor remains masked upon creation. `rt_intr_enable()` should be called for the new interrupt object to unmask it.

4.6.1.3 `int rt_intr_create (RT_INTR * intr, const char * name, unsigned irq, rt_isr_t isr, rt_iack_t iack, int mode)`

Create an interrupt object from kernel space.

Initializes and associates an interrupt object with an IRQ line. In kernel space, interrupts are immediately notified to a user-defined handler or ISR (interrupt service routine).

When an interrupt occurs on the given *irq* line, the ISR is fired in order to deal with the hardware event. The interrupt service code may call any non-suspensive Xenomai service.

Upon receipt of an IRQ, the ISR is immediately called on behalf of the interrupted stack context, the rescheduling procedure is locked, and the interrupt source is masked at hardware level. The status value returned by the ISR is then checked for the following values:

- `RT_INTR_HANDLED` indicates that the interrupt request has been fulfilled by the ISR.
- `RT_INTR_NONE` indicates the opposite to `RT_INTR_HANDLED`. The ISR must always return this value when it determines that the interrupt request has not been issued by the dedicated hardware device.

In addition, one of the following bits may be set by the ISR :

NOTE: use these bits with care and only when you do understand their effect on the system. The ISR is not encouraged to use these bits in case it shares the IRQ line with other ISRs in the real-time domain.

- `RT_INTR_PROPAGATE` tells Xenomai to require the real-time control layer to forward the IRQ. For instance, this would cause the Adeos control layer to propagate the interrupt down the interrupt pipeline to other Adeos domains, such as Linux. This is the regular way to share interrupts between Xenomai and the Linux kernel.
- `RT_INTR_NOENABLE` asks Xenomai not to re-enable the IRQ line upon return of the interrupt service routine.

A count of interrupt receipts is tracked into the interrupt descriptor, and reset to zero each time the interrupt object is attached. Since this count could wrap around, it should be used as an indication of interrupt activity only.

Parameters:

intr The address of a interrupt object descriptor Xenomai will use to store the object-specific data. This descriptor must always be valid while the object is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the interrupt object. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created interrupt objects.

irq The hardware interrupt channel associated with the interrupt object. This value is architecture-dependent.

isr The address of a valid interrupt service routine in kernel space. This handler will be called each time the corresponding IRQ is delivered on behalf of an interrupt context. A pointer to an internal information is passed to the routine which can use it to retrieve the descriptor address of the associated interrupt object through the `I_DESC()` macro.

iack The address of an optional interrupt acknowledge routine, aimed at replacing the default one. Only very specific situations actually require to override the default setting for this parameter, like having to acknowledge non-standard PIC hardware. *iack* should return a non-zero value to indicate that the interrupt has been properly acknowledged. If *iack* is NULL, the default routine will be used instead.

mode The interrupt object creation mode. The following flags can be OR'ed into this bitmask, each of them affecting the new interrupt object:

- `I_SHARED` enables IRQ-sharing with other interrupt objects.
- `I_EDGE` is an additional flag need to be set together with `I_SHARED` to enable IRQ-sharing of edge-triggered interrupts.

Returns:

0 is returned upon success. Otherwise:

- `-ENOMEM` is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the interrupt object.
- `-EBUSY` is returned if the interrupt line is already in use by another interrupt object. Only a single interrupt object can be associated to any given interrupt line using `rt_intr_create()` at any time.
- `-EEXIST` is returned if *irq* is already associated to an existing interrupt object.
- `-EPERM` is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

Note:

The interrupt source associated to the interrupt descriptor remains masked upon creation. `rt_intr_enable()` should be called for the new interrupt object to unmask it.

4.6.1.4 `int rt_intr_delete (RT_INTR * intr)`

Delete an interrupt object.

Destroys an interrupt object. An interrupt exists in the system since `rt_intr_create()` has been called to create it, so this service must be called in order to destroy it afterwards.

Any user-space task which might be currently pending on the interrupt object through the `rt_intr_wait()` service will be awoken as a result of the deletion, and return with the `-EIDRM` status.

Parameters:

intr The descriptor address of the affected interrupt object.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *intr* is not a interrupt object descriptor.
- -EIDRM is returned if *intr* is a deleted interrupt object descriptor.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.6.1.5 `int rt_intr_disable (RT_INTR * intr)`

Disable an interrupt object.

Disables the hardware interrupt line associated with an interrupt object. This operation invalidates further interrupt requests from the given source until the IRQ line is re-enabled anew through [rt_intr_enable\(\)](#).

Parameters:

intr The descriptor address of the interrupt object to enable.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *intr* is not a interrupt object descriptor.
- -EIDRM is returned if *intr* is a deleted interrupt object descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: never.

4.6.1.6 `int rt_intr_enable (RT_INTR * intr)`

Enable an interrupt object.

Enables the hardware interrupt line associated with an interrupt object. Over Adeos-based systems which mask and acknowledge IRQs upon receipt, this operation is necessary to revalidate the interrupt channel so that more interrupts from the same source can be notified.

Parameters:

intr The descriptor address of the interrupt object to enable.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *intr* is not a interrupt object descriptor.
- -EIDRM is returned if *intr* is a deleted interrupt object descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: never.

4.6.1.7 `int rt_intr_inquire (RT_INTR * intr, RT_INTR_INFO * info)`

Inquire about an interrupt object.

Return various information about the status of a given interrupt object.

Parameters:

intr The descriptor address of the inquired interrupt object.

info The address of a structure the interrupt object information will be written to.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success. Otherwise:

- -EINVAL is returned if *intr* is not a interrupt object descriptor.
- -EIDRM is returned if *intr* is a deleted interrupt object descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.6.1.8 `int rt_intr_unbind (RT_INTR * intr) [inline, static]`

Unbind from an interrupt object.

This user-space only service unbinds the calling task from the interrupt object previously retrieved by a call to `rt_intr_bind()`.

Parameters:

intr The address of a interrupt object descriptor to unbind from.

Returns:

0 is always returned.

This service can be called from:

- User-space task.

Rescheduling: never.

4.6.1.9 `int rt_intr_wait (RT_INTR * intr, RTIME timeout)`

Wait for the next interrupt.

This user-space only call allows the current task to suspend execution until the associated interrupt event triggers. The priority of the current task is raised above all other Xenomai tasks - except those also undergoing an interrupt or alarm wait (see `rt_alarm_wait()`) - so that it would preempt any of them under normal circumstances (i.e. no scheduler lock).

Interrupt receipts are logged if they cannot be delivered immediately to some interrupt server task, so that a call to `rt_intr_wait()` might return immediately if an IRQ is already pending on entry of the service.

Parameters:

intr The descriptor address of the awaited interrupt.

timeout The number of clock ticks to wait for an interrupt to occur (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until an interrupt triggers. Passing `TM_NONBLOCK` is invalid.

Returns:

A positive value is returned upon success, representing the number of pending interrupts to process. Otherwise:

- -ETIMEDOUT is returned if no interrupt occurred within the specified amount of time.
- -EINVAL is returned if *intr* is not an interrupt object descriptor, or *timeout* is equal to TM_NONBLOCK.
- -EIDRM is returned if *intr* is a deleted interrupt object descriptor, including if the deletion occurred while the caller was waiting for its next interrupt.
- -EINTR is returned if [rt_task_unblock\(\)](#) has been called for the current task before the next interrupt occurrence.

Environments:

This service can be called from:

- User-space task


Rescheduling: always, unless an interrupt is already pending on entry.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.7 Native Xenomai API.

Collaboration diagram for Native Xenomai API.:



4.7.1 Detailed Description

The native Xenomai programming interface available to real-time applications. This API is built over the abstract RTOS core implemented by the Xenomai nucleus.

Modules

- [Task Status](#)
Defines used to specify task state and/or mode.
- [Alarm services.](#)
- [Condition variable services.](#)
- [Event flag group services.](#)
- [Memory heap services.](#)
- [Interrupt management services.](#)
- [Mutex services.](#)
- [Message pipe services.](#)
- [Message queue services.](#)
- [Counting semaphore services.](#)
- [Task management services.](#)
- [Timer management services.](#)

4.8 Mutex services.

Collaboration diagram for Mutex services.:



4.8.1 Detailed Description

Mutex services.

A mutex is a MUTual EXclusion object, and is useful for protecting shared data structures from concurrent modifications, and implementing critical sections and monitors.

A mutex has two possible states: unlocked (not owned by any task), and locked (owned by one task). A mutex can never be owned by two different tasks simultaneously. A task attempting to lock a mutex that is already locked by another task is blocked until the latter unlocks the mutex first.

Xenomai mutex services enforce a priority inheritance protocol in order to solve priority inversions.

Files

- file [mutex.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_mutex_create](#) (RT_MUTEX *mutex, const char *name)
- int [rt_mutex_delete](#) (RT_MUTEX *mutex)
- int [rt_mutex_acquire](#) (RT_MUTEX *mutex, RTIME timeout)
- int [rt_mutex_release](#) (RT_MUTEX *mutex)
- int [rt_mutex_inquire](#) (RT_MUTEX *mutex, RT_MUTEX_INFO *info)
- int [rt_mutex_bind](#) (RT_MUTEX *mutex, const char *name, RTIME timeout)
- static int [rt_mutex_unbind](#) (RT_MUTEX *mutex)

4.8.2 Function Documentation

4.8.2.1 int [rt_mutex_acquire](#) (RT_MUTEX * *mutex*, RTIME *timeout*)

Acquire a mutex.

Attempt to lock a mutex. The calling task is blocked until the mutex is available, in which case it is locked again before this service returns. Mutexes have an ownership property, which means that their current owner is tracked. Xenomai mutexes are implicitly recursive and implement the priority inheritance protocol.

Since a nested locking count is maintained for the current owner, [rt_mutex_acquire\(\)](#) and [rt_mutex_release\(\)](#) must be used in pairs.

Tasks pend on mutexes by priority order.

Parameters:

mutex The descriptor address of the mutex to acquire.

timeout The number of clock ticks to wait for the mutex to be available to the calling task (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until the mutex is available. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if the mutex is still locked by another task.

Returns:

0 is returned upon success. Otherwise:

- `-EINVAL` is returned if *mutex* is not a mutex descriptor.
- `-EIDRM` is returned if *mutex* is a deleted mutex descriptor, including if the deletion occurred while the caller was sleeping on it.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and the mutex is not immediately available.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before the mutex has become available.
- `-ETIMEDOUT` is returned if the mutex cannot be made available to the calling task within the specified amount of time.
- `-EPERM` is returned if this service was called from a context which cannot be given the ownership of the mutex (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation. If the caller is blocked, the current owner's priority might be temporarily raised as a consequence of the priority inheritance protocol.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.8.2.2 `int rt_mutex_bind (RT_MUTEX * mutex, const char * name, RTIME timeout)`

Bind to a mutex.

This user-space only service retrieves the uniform descriptor of a given Xenomai mutex identified by its symbolic name. If the mutex does not exist on entry, this service blocks the caller until a mutex of the given name is created.

Parameters:

name A valid NULL-terminated name which identifies the mutex to bind to.

mutex The address of a mutex descriptor retrieved by the operation. Contents of this memory is undefined upon failure.

timeout The number of clock ticks to wait for the registration to occur (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until the object is registered. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if the object is not registered on entry.

Returns:

0 is returned upon success. Otherwise:

- `-EFAULT` is returned if *mutex* or *name* is referencing invalid memory.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before the retrieval has completed.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and the searched object is not registered on entry.
- `-ETIMEDOUT` is returned if the object cannot be retrieved within the specified amount of time.
- `-EPERM` is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.8.2.3 `int rt_mutex_create (RT_MUTEX * mutex, const char * name)`

Create a mutex.

Create a mutual exclusion object that allows multiple tasks to synchronize access to a shared resource. A mutex is left in an unlocked state after creation.

Parameters:

mutex The address of a mutex descriptor Xenomai will use to store the mutex-related data. This descriptor must always be valid while the mutex is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the mutex. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created mutex.

Returns:

0 is returned upon success. Otherwise:

- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the mutex.
- -EEXIST is returned if the *name* is already in use by some registered object.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.8.2.4 `int rt_mutex_delete (RT_MUTEX * mutex)`

Delete a mutex.

Destroy a mutex and release all the tasks currently pending on it. A mutex exists in the system since `rt_mutex_create()` has been called to create it, so this service must be called in order to destroy it afterwards.

Parameters:

mutex The descriptor address of the affected mutex.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *mutex* is not a mutex descriptor.
- -EIDRM is returned if *mutex* is a deleted mutex descriptor.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.8.2.5 `int rt_mutex_inquire (RT_MUTEX * mutex, RT_MUTEX_INFO * info)`

Inquire about a mutex.

Return various information about the status of a given mutex.

Parameters:

mutex The descriptor address of the inquired mutex.

info The address of a structure the mutex information will be written to.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success.
Otherwise:

- -EINVAL is returned if *mutex* is not a mutex descriptor.
- -EIDRM is returned if *mutex* is a deleted mutex descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.8.2.6 `int rt_mutex_release (RT_MUTEX * mutex)`

Unlock mutex.

Release a mutex. If the mutex is pended, the first waiting task (by priority order) is immediately unblocked and transferred the ownership of the mutex; otherwise, the mutex is left in an unlocked state.

Parameters:

mutex The descriptor address of the released mutex.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *mutex* is not a mutex descriptor.
- -EIDRM is returned if *mutex* is a deleted mutex descriptor.
- -EPERM is returned if *mutex* is not owned by the current task, or more generally if this service was called from a context which cannot own any mutex (e.g. interrupt, or non-realtime context).

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: possible.

4.8.2.7 `int rt_mutex_unbind (RT_MUTEX * mutex)` [inline, static]

Unbind from a mutex.

This user-space only service unbinds the calling task from the mutex object previously retrieved by a call to [rt_mutex_bind\(\)](#).

Parameters:

mutex The address of a mutex descriptor to unbind from.

Returns:

0 is always returned.

This service can be called from:

- User-space task.

Rescheduling: never.

4.9 Message pipe services.

Collaboration diagram for Message pipe services.:



4.9.1 Detailed Description

Message pipe services.

A message pipe is a two-way communication channel between Xenomai tasks and standard Linux processes using regular file I/O operations on a pseudo-device. Pipes can be operated in a message-oriented fashion so that message boundaries are preserved, and also in byte streaming mode from real-time to standard Linux processes for optimal throughput.

Xenomai tasks open their side of the pipe using the `rt_pipe_create()` service; standard Linux processes do the same by opening one of the `/dev/rtpN` special devices, where N is the minor number agreed upon between both ends of each pipe. Additionally, named pipes are available through the registry support, which automatically creates a symbolic link from entries under `/proc/xenomai/registry/native/pipes/` to the corresponding special device file.

Files

- file [pipe.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_pipe_create](#) (RT_PIPE *pipe, const char *name, int minor, size_t poolsize)
- int [rt_pipe_delete](#) (RT_PIPE *pipe)
- ssize_t [rt_pipe_receive](#) (RT_PIPE *pipe, RT_PIPE_MSG **msgp, RTIME timeout)
- ssize_t [rt_pipe_read](#) (RT_PIPE *pipe, void *buf, size_t size, RTIME timeout)
- ssize_t [rt_pipe_send](#) (RT_PIPE *pipe, RT_PIPE_MSG *msg, size_t size, int mode)
- ssize_t [rt_pipe_write](#) (RT_PIPE *pipe, const void *buf, size_t size, int mode)
- ssize_t [rt_pipe_stream](#) (RT_PIPE *pipe, const void *buf, size_t size)
- ssize_t [rt_pipe_flush](#) (RT_PIPE *pipe)
- RT_PIPE_MSG * [rt_pipe_alloc](#) (RT_PIPE *pipe, size_t size)
- int [rt_pipe_free](#) (RT_PIPE *pipe, RT_PIPE_MSG *msg)

4.9.2 Function Documentation

4.9.2.1 RT_PIPE_MSG * [rt_pipe_alloc](#) (RT_PIPE * pipe, size_t size)

Allocate a message pipe buffer.

This service allocates a message buffer from the pipe's heap which can be subsequently filled by the caller then passed to [rt_pipe_send\(\)](#) for sending. The beginning of the available data area of `size` contiguous bytes is accessible from `P_MSGPTR(msg)`.

Parameters:

pipe The descriptor address of the affected pipe.

size The requested size in bytes of the buffer. This value should represent the size of the payload data.

Returns:

The address of the allocated message buffer upon success, or NULL if the allocation fails.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task

Rescheduling: never.

4.9.2.2 int rt_pipe_create (RT_PIPE * pipe, const char * name, int minor, size_t poolsize)

Create a message pipe.

This service opens a bi-directional communication channel allowing data exchange between Xenomai tasks and standard Linux processes. Pipes natively preserve message boundaries, but can also be used in byte stream mode from Xenomai tasks to standard Linux processes.

`rt_pipe_create()` always returns immediately, even if no Linux process has opened the associated special device file yet. On the contrary, the non real-time side could block upon attempt to open the special device file until `rt_pipe_create()` is issued on the same pipe from a Xenomai task, unless `O_NONBLOCK` has been specified to the `open(2)` system call.

Parameters:

pipe The address of a pipe descriptor Xenomai will use to store the pipe-related data. This descriptor must always be valid while the pipe is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the message pipe. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created pipe.

Named pipes are supported through the use of the registry. When the registry support is enabled, passing a valid *name* parameter when creating a message pipe subsequently allows standard Linux processes to follow a symbolic link from `/proc/xenomai/registry/pipes/name` in order to reach the associated special device (i.e. `/dev/rtp*`), so that the specific *minor* information does not need to be known from those processes for opening the proper device file. In such a case, both sides of the pipe only need to agree upon a symbolic name to refer to the same data path, which is especially useful whenever the *minor* number is picked up dynamically using an adaptive algorithm, such as passing `P_MINOR_AUTO` as *minor* value.

Parameters:

minor The minor number of the device associated with the pipe. Passing `P_MINOR_AUTO` causes the minor number to be auto-allocated. In such a case, the *name* parameter must

be valid so that user-space processes may subsequently follow the symbolic link that will be automatically created from `/proc/xenomai/registry/pipes/name` to the allocated pipe device entry (i.e. `/dev/rtp*`).

poolsize Specifies the size of a dedicated buffer pool for the pipe. Passing 0 means that all message allocations for this pipe are performed on the system heap.

Returns:

0 is returned upon success. Otherwise:

- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the pipe, or if not enough memory could be obtained from the selected buffer pool for allocating the internal streaming buffer.
- -EEXIST is returned if the *name* is already in use by some registered object.
- -ENODEV is returned if *minor* is different from P_MINOR_AUTO and is not a valid minor number for the pipe special device either (i.e. `/dev/rtp*`).
- -EBUSY is returned if *minor* is already open.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.9.2.3 `int rt_pipe_delete (RT_PIPE * pipe)`

Delete a message pipe.

This service deletes a pipe previously created by `rt_pipe_create()`. Data pending for transmission to non real-time processes are lost.

Parameters:

pipe The descriptor address of the affected pipe.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *pipe* is not a pipe descriptor.
- -EIDRM is returned if *pipe* is a closed pipe descriptor.

- -ENODEV or -EBADF can be returned if *pipe* is scrambled.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.9.2.4 `ssize_t rt_pipe_flush (RT_PIPE * pipe)`

Flush the pipe.

This operation makes the data available for reading from the associated special device.

Parameters:

pipe The descriptor address of the pipe to flush.

Returns:

Zero upon success. Otherwise:

- -EINVAL is returned if *pipe* is not a pipe descriptor.
- -EPIPE is returned if the associated special device is not yet open.
- -EIDRM is returned if *pipe* is a closed pipe descriptor.
- -ENODEV or -EBADF are returned if *pipe* is scrambled.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task

Rescheduling: possible.

Note:

This service is deprecated, since the streamed data is now immediately available to the receiving side.

4.9.2.5 `int rt_pipe_free (RT_PIPE * pipe, RT_PIPE_MSG * msg)`

Free a message pipe buffer.

This service releases a message buffer returned by `rt_pipe_receive()` to the pipe's heap.

Parameters:

pipe The descriptor address of the affected pipe.

msg The address of the message buffer to free.

Returns:

0 is returned upon success, or `-EINVAL` if *msg* is not a valid message buffer previously allocated by the `rt_pipe_alloc()` service.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task

Rescheduling: never.

4.9.2.6 `ssize_t rt_pipe_read (RT_PIPE * pipe, void * buf, size_t size, RTIME timeout)`

Read a message from a pipe.

This service retrieves the next message written to the associated special device in user-space. `rt_pipe_read()` always preserves message boundaries, which means that all data sent through the same `write(2)` operation to the special device will be gathered in a single message by this service. This service differs from `rt_pipe_receive()` in that it copies back the payload data to a user-defined memory area, instead of returning a pointer to the internal message buffer holding such data.

Unless otherwise specified, the caller is blocked for a given amount of time if no data is immediately available on entry.

Parameters:

pipe The descriptor address of the pipe to read from.

buf A pointer to a memory location which will be written upon success with the read message contents.

size The count of bytes from the received message to read up into *buf*. If *size* is lower than the actual message size, `-ENOBUFFS` is returned since the incompletely received message would be lost. If *size* is zero, this call returns immediately with no other action.

timeout The number of clock ticks to wait for some message to arrive (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until some data is eventually available. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if no data is available on entry.

Returns:

The number of read bytes copied to the *buf* is returned upon success. Otherwise:

- -EINVAL is returned if *pipe* is not a pipe descriptor.
- -EIDRM is returned if *pipe* is a closed pipe descriptor.
- -ENODEV or -EBADF are returned if *pipe* is scrambled.
- -ETIMEDOUT is returned if *timeout* is different from TM_NONBLOCK and no data is available within the specified amount of time.
- -EWOULDBLOCK is returned if *timeout* is equal to TM_NONBLOCK and no data is immediately available on entry.
- -EINTR is returned if [rt_task_unblock\(\)](#) has been called for the waiting task before any data was available.
- -EPERM is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).
- -ENOBUFS is returned if *size* is not large enough to collect the message data.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *timeout* is equal to TM_NONBLOCK.
- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.9.2.7 ssize_t rt_pipe_receive (RT_PIPE * pipe, RT_PIPE_MSG ** msgp, RTIME timeout)

Receive a message from a pipe.

This service retrieves the next message written to the associated special device in user-space. [rt_pipe_receive\(\)](#) always preserves message boundaries, which means that all data sent through the same write(2) operation to the special device will be gathered in a single message by this

service. This service differs from `rt_pipe_read()` in that it returns a pointer to the internal buffer holding the message, which improves performances by saving a data copy to a user-provided buffer, especially when large messages are involved.

Unless otherwise specified, the caller is blocked for a given amount of time if no data is immediately available on entry.

Parameters:

pipe The descriptor address of the pipe to receive from.

msgp A pointer to a memory location which will be written upon success with the address of the received message. Once consumed, the message space should be freed using `rt_pipe_free()`. The application code can retrieve the actual data and size carried by the message by respectively using the `P_MSGPTR()` and `P_MSGSIZE()` macros.

timeout The number of clock ticks to wait for some message to arrive (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until some data is eventually available. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if no data is available on entry.

Returns:

The number of read bytes available from the received message is returned upon success; this value will be equal to `P_MSGSIZE(*msgp)`. Otherwise:

- `-EINVAL` is returned if *pipe* is not a pipe descriptor.
- `-EIDRM` is returned if *pipe* is a closed pipe descriptor.
- `-ENODEV` or `-EBADF` are returned if *pipe* is scrambled.
- `-ETIMEDOUT` is returned if *timeout* is different from `TM_NONBLOCK` and no data is available within the specified amount of time.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and no data is immediately available on entry.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before any data was available.
- `-EPERM` is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *timeout* is equal to `TM_NONBLOCK`.
- Kernel-based task

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.9.2.8 `ssize_t rt_pipe_send (RT_PIPE * pipe, RT_PIPE_MSG * msg, size_t size, int mode)`

Send a message through a pipe.

This service writes a complete message to be received from the associated special device. `rt_pipe_send()` always preserves message boundaries, which means that all data sent through a single call of this service will be gathered in a single `read(2)` operation from the special device. This service differs from `rt_pipe_write()` in that it accepts a canned message buffer, instead of a pointer to the raw data to be sent. This call is useful whenever the caller wants to prepare the message contents separately from its sending, which does not require to have all the data to be sent available at once but allows for incremental updates of the message, and also saves a message copy, since `rt_pipe_send()` deals internally with message buffers.

Parameters:

pipe The descriptor address of the pipe to send to.

msg The address of the message to be sent. The message space must have been allocated using the `rt_pipe_alloc()` service. Once passed to `rt_pipe_send()`, the memory pointed to by *msg* is no more under the control of the application code and thus should not be referenced by it anymore; deallocation of this memory will be automatically handled as needed. As a special exception, *msg* can be NULL and will not be dereferenced if *size* is zero.

size The size in bytes of the message (payload data only). Zero is a valid value, in which case the service returns immediately without sending any message. This parameter allows you to actually send less data than you reserved using the `rt_pipe_alloc()` service, which may be the case if you did not know how much space you needed at the time of allocation. In all other cases it may be more convenient to just pass `P_MSGSIZE(msg)`.

mode A set of flags affecting the operation:

- `P_URGENT` causes the message to be prepended to the output queue, ensuring a LIFO ordering.
- `P_NORMAL` causes the message to be appended to the output queue, ensuring a FIFO ordering.

Returns:

Upon success, this service returns *size*. Upon error, one of the following error codes is returned:

- `-EINVAL` is returned if *pipe* is not a pipe descriptor.
- `-EPIPE` is returned if the associated special device is not yet open.
- `-EIDRM` is returned if *pipe* is a closed pipe descriptor.

- -ENODEV or -EBADF are returned if *pipe* is scrambled.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task

Rescheduling: possible.

4.9.2.9 `ssize_t rt_pipe_stream (RT_PIPE * pipe, const void * buf, size_t size)`

Stream bytes to a pipe.

This service writes a sequence of bytes to be received from the associated special device. Unlike `rt_pipe_send()`, this service does not preserve message boundaries. Instead, an internal buffer is filled on the fly with the data, which will be consumed as soon as the receiver wakes up.

Data buffers sent by the `rt_pipe_stream()` service are always transmitted in FIFO order (i.e. P_-NORMAL mode).

Parameters:

pipe The descriptor address of the pipe to write to.

buf The address of the first data byte to send. The data will be copied to an internal buffer before transmission.

size The size in bytes of the buffer. Zero is a valid value, in which case the service returns immediately without buffering any data.

Returns:

The number of bytes sent upon success; this value may be lower than *size*, depending on the available space in the internal buffer. Otherwise:

- -EINVAL is returned if *pipe* is not a pipe descriptor.
- -EPIPE is returned if the associated special device is not yet open.
- -EIDRM is returned if *pipe* is a closed pipe descriptor.
- -ENODEV or -EBADF are returned if *pipe* is scrambled.
- -ENOSYS is returned if the byte streaming mode has been disabled at configuration time by nullifying the size of the pipe buffer (see `CONFIG_XENO_OPT_NATIVE_PIPE_BUFSZ`).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code

- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.9.2.10 `ssize_t rt_pipe_write (RT_PIPE * pipe, const void * buf, size_t size, int mode)`

Write a message to a pipe.

This service writes a complete message to be received from the associated special device. `rt_pipe_write()` always preserves message boundaries, which means that all data sent through a single call of this service will be gathered in a single `read(2)` operation from the special device. This service differs from `rt_pipe_send()` in that it accepts a pointer to the raw data to be sent, instead of a canned message buffer. This call is useful whenever the caller does not need to prepare the message contents separately from its sending.

Parameters:

pipe The descriptor address of the pipe to write to.

buf The address of the first data byte to send. The data will be copied to an internal buffer before transmission.

size The size in bytes of the message (payload data only). Zero is a valid value, in which case the service returns immediately without sending any message.

mode A set of flags affecting the operation:

- `P_URGENT` causes the message to be prepended to the output queue, ensuring a LIFO ordering.
- `P_NORMAL` causes the message to be appended to the output queue, ensuring a FIFO ordering.

Returns:

Upon success, this service returns *size*. Upon error, one of the following error codes is returned:

- `-EINVAL` is returned if *pipe* is not a pipe descriptor.
- `-EPIPE` is returned if the associated special device is not yet open.
- `-ENOMEM` is returned if not enough buffer space is available to complete the operation.
- `-EIDRM` is returned if *pipe* is a closed pipe descriptor.
- `-ENODEV` or `-EBADF` are returned if *pipe* is scrambled.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.10 Message queue services.

Collaboration diagram for Message queue services.:



4.10.1 Detailed Description

Queue services.

Message queueing is a method by which real-time tasks can exchange or pass data through a Xenomai-managed queue of messages. Messages can vary in length and be assigned different types or usages. A message queue can be created by one task and used by multiple tasks that send and/or receive messages to the queue.

This implementation is based on a zero-copy scheme for message buffers. Message buffer pools are built over the nucleus's heap objects, which in turn provide the needed support for exchanging messages between kernel and user-space using direct memory mapping.

Files

- file [queue.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_queue_create](#) (RT_QUEUE *q, const char *name, size_t poolsize, size_t qlimit, int mode)
- int [rt_queue_delete](#) (RT_QUEUE *q)
- void * [rt_queue_alloc](#) (RT_QUEUE *q, size_t size)
- int [rt_queue_free](#) (RT_QUEUE *q, void *buf)
- int [rt_queue_send](#) (RT_QUEUE *q, void *mbuf, size_t size, int mode)
- int [rt_queue_write](#) (RT_QUEUE *q, const void *buf, size_t size, int mode)
- ssize_t [rt_queue_receive](#) (RT_QUEUE *q, void **bufp, RTIME timeout)
- ssize_t [rt_queue_read](#) (RT_QUEUE *q, void *buf, size_t size, RTIME timeout)
- int [rt_queue_inquire](#) (RT_QUEUE *q, RT_QUEUE_INFO *info)
- int [rt_queue_bind](#) (RT_QUEUE *q, const char *name, RTIME timeout)
- int [rt_queue_unbind](#) (RT_QUEUE *q)

4.10.2 Function Documentation

4.10.2.1 void* [rt_queue_alloc](#) (RT_QUEUE *q, size_t size)

Allocate a message queue buffer.

This service allocates a message buffer from the queue's internal pool which can be subsequently filled by the caller then passed to [rt_queue_send\(\)](#) for sending.

Parameters:

- q* The descriptor address of the affected queue.
- size* The requested size in bytes of the buffer. Zero is an acceptable value, meaning that the message will not carry any payload data; the receiver will thus receive a zero-sized message.

Returns:

The address of the allocated message buffer upon success, or NULL if the allocation fails.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.10.2.2 int rt_queue_bind (RT_QUEUE * *q*, const char * *name*, RTIME *timeout*)

Bind to a shared message queue.

This user-space only service retrieves the uniform descriptor of a given shared Xenomai message queue identified by its symbolic name. If the queue does not exist on entry, this service blocks the caller until a queue of the given name is created.

Parameters:

- name* A valid NULL-terminated name which identifies the queue to bind to.
- q* The address of a queue descriptor retrieved by the operation. Contents of this memory is undefined upon failure.
- timeout* The number of clock ticks to wait for the registration to occur (see note). Passing TM_INFINITE causes the caller to block indefinitely until the object is registered. Passing TM_NONBLOCK causes the service to return immediately without waiting if the object is not registered on entry.

Returns:

0 is returned upon success. Otherwise:

- -EFAULT is returned if *q* or *name* is referencing invalid memory.
- -EINTR is returned if [rt_task_unblock\(\)](#) has been called for the waiting task before the retrieval has completed.
- -EWOULDBLOCK is returned if *timeout* is equal to TM_NONBLOCK and the searched object is not registered on entry.

- -ETIMEDOUT is returned if the object cannot be retrieved within the specified amount of time.
- -EPERM is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).
- -ENOENT is returned if the special file /dev/rtheap (character-mode, major 10, minor 254) is not available from the filesystem. This device is needed to map the memory pool used by the shared queue into the caller's address space. udev-based systems should not need manual creation of such device entry.

Environments:

This service can be called from:

- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.10.2.3 `int rt_queue_create (RT_QUEUE * q, const char * name, size_t poolsize, size_t qlimit, int mode)`

Create a message queue.

Create a message queue object that allows multiple tasks to exchange data through the use of variable-sized messages. A message queue is created empty. Message queues can be local to the kernel space, or shared between kernel and user-space.

This service needs the special character device /dev/rtheap (10,254) when called from user-space tasks.

Parameters:

q The address of a queue descriptor Xenomai will use to store the queue-related data. This descriptor must always be valid while the message queue is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the queue. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created queue. Shared queues must be given a valid name.

poolsize The size (in bytes) of the message buffer pool which is going to be pre-allocated to the queue. Message buffers will be claimed and released to this pool. The buffer pool memory is not extensible, so this value must be compatible with the highest message pressure that could be expected.

qlimit This parameter allows to limit the maximum number of messages which can be queued at any point in time. Sending to a full queue begets an error. The special value Q_UNLIMITED can be passed to specify an unlimited amount.

mode The queue creation mode. The following flags can be OR'ed into this bitmask, each of them affecting the new queue:

- `Q_FIFO` makes tasks pend in FIFO order on the queue for consuming messages.
- `Q_PRIO` makes tasks pend in priority order on the queue.
- `Q_SHARED` causes the queue to be sharable between kernel and user-space tasks. Otherwise, the new queue is only available for kernel-based usage. This flag is implicitly set when the caller is running in user-space. This feature requires the real-time support in user-space to be configured in (`CONFIG_XENO_OPT_PERVASIVE`).
- `Q_DMA` causes the buffer pool associated to the queue to be allocated in physically contiguous memory, suitable for DMA operations with I/O devices. A 128Kb limit exists for *poolsize* when this flag is passed.

Returns:

0 is returned upon success. Otherwise:

- `-EEXIST` is returned if the *name* is already in use by some registered object.
- `-EINVAL` is returned if *poolsize* is null, greater than the system limit, or *name* is null or empty for a shared queue.
- `-ENOMEM` is returned if not enough system memory is available to create or register the queue. Additionally, and if `Q_SHARED` has been passed in *mode*, errors while mapping the buffer pool in the caller's address space might beget this return code too.
- `-EPERM` is returned if this service was called from an invalid context.
- `-ENOSYS` is returned if *mode* specifies `Q_SHARED`, but the real-time support in user-space is unavailable.
- `-ENOENT` is returned if `/dev/rtheap` can't be opened.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- User-space task (switches to secondary mode)

Rescheduling: possible.

4.10.2.4 `int rt_queue_delete (RT_QUEUE * q)`

Delete a message queue.

Destroy a message queue and release all the tasks currently pending on it. A queue exists in the system since `rt_queue_create()` has been called to create it, so this service must be called in order to destroy it afterwards.

Parameters:

q The descriptor address of the affected queue.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *q* is not a message queue descriptor.
- -EIDRM is returned if *q* is a deleted queue descriptor.
- -EPERM is returned if this service was called from an asynchronous context.
- -EBUSY is returned if an attempt is made to delete a shared queue which is still bound to a process.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- User-space task (switches to secondary mode).

Rescheduling: possible.

4.10.2.5 int rt_queue_free (RT_QUEUE * *q*, void * *buf*)

Free a message queue buffer.

This service releases a message buffer returned by [rt_queue_receive\(\)](#) to the queue's internal pool.

Parameters:

q The descriptor address of the affected queue.

buf The address of the message buffer to free. Even zero-sized messages carrying no payload data must be freed, since they are assigned a valid memory space to store internal information.

Returns:

0 is returned upon success, or -EINVAL if *buf* is not a valid message buffer previously allocated by the [rt_queue_alloc\(\)](#) service, or the caller did not get ownership of the message through a successful return from [rt_queue_receive\(\)](#).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.10.2.6 `int rt_queue_inquire (RT_QUEUE * q, RT_QUEUE_INFO * info)`

Inquire about a message queue.

Return various information about the status of a given queue.

Parameters:

q The descriptor address of the inquired queue.

info The address of a structure the queue information will be written to.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success. Otherwise:

- -EINVAL is returned if *q* is not a message queue descriptor.
- -EIDRM is returned if *q* is a deleted queue descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.10.2.7 `ssize_t rt_queue_read (RT_QUEUE * q, void * buf, size_t size, RTIME timeout)`

Read a message from a queue.

This service retrieves the next message available from the given queue. Unless otherwise specified, the caller is blocked for a given amount of time if no message is immediately available on entry. This services differs from `rt_queue_receive()` in that it copies back the payload data to a user-defined memory area, instead of returning a pointer to the message buffer holding such data.

Parameters:

q The descriptor address of the message queue to read from.

buf A pointer to a memory area which will be written upon success with the message contents. The internal message buffer conveying the data is automatically freed by this call.

size The length in bytes of the memory area pointed to by *buf*. Messages larger than *size* are truncated appropriately.

timeout The number of clock ticks to wait for some message to arrive (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until some message is eventually available. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if no message is available on entry.

Returns:

The number of bytes available from the received message is returned upon success, which might be greater than the actual number of bytes copied to the destination buffer if the message has been truncated. Zero is a possible value corresponding to a zero-sized message passed to `rt_queue_send()` or `rt_queue_write()`. Otherwise:

- -EINVAL is returned if *q* is not a message queue descriptor.
- -EIDRM is returned if *q* is a deleted queue descriptor.
- -ETIMEDOUT is returned if *timeout* is different from TM_NONBLOCK and no message is available within the specified amount of time.
- -EWOULDBLOCK is returned if *timeout* is equal to TM_NONBLOCK and no message is immediately available on entry.
- -EINTR is returned if `rt_task_unblock()` has been called for the waiting task before any data was available.
- -EPERM is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *timeout* is equal to TM_NONBLOCK.
- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.10.2.8 ssize_t rt_queue_receive (RT_QUEUE * *q*, void ** *bufp*, RTIME *timeout*)

Receive a message from a queue.

This service retrieves the next message available from the given queue. Unless otherwise specified, the caller is blocked for a given amount of time if no message is immediately available on entry.

Parameters:

q The descriptor address of the message queue to receive from.

bufp A pointer to a memory location which will be written upon success with the address of the received message. Once consumed, the message space should be freed using `rt_queue_free()`.

timeout The number of clock ticks to wait for some message to arrive (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until some message is eventually available. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if no message is available on entry.

Returns:

The number of bytes available from the received message is returned upon success. Zero is a possible value corresponding to a zero-sized message passed to `rt_queue_send()`. Otherwise:

- `-EINVAL` is returned if *q* is not a message queue descriptor.
- `-EIDRM` is returned if *q* is a deleted queue descriptor.
- `-ETIMEDOUT` is returned if *timeout* is different from `TM_NONBLOCK` and no message is available within the specified amount of time.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and no message is immediately available on entry.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before any data was available.
- `-EPERM` is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *timeout* is equal to `TM_NONBLOCK`.
- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.10.2.9 `int rt_queue_send (RT_QUEUE * q, void * mbuf, size_t size, int mode)`

Send a message to a queue.

This service sends a complete message to a given queue. The message must have been allocated by a previous call to `rt_queue_alloc()`.

Parameters:

q The descriptor address of the message queue to send to.

mbuf The address of the message buffer to be sent. The message buffer must have been allocated using the `rt_queue_alloc()` service. Once passed to `rt_queue_send()`, the memory pointed to by *mbuf* is no more under the control of the sender and thus should not be referenced by it anymore; deallocation of this memory must be handled on the receiving side.

size The size in bytes of the message. Zero is a valid value, in which case an empty message will be sent.

mode A set of flags affecting the operation:

- `Q_URGENT` causes the message to be prepended to the message queue, ensuring a LIFO ordering.
- `Q_NORMAL` causes the message to be appended to the message queue, ensuring a FIFO ordering.
- `Q_BROADCAST` causes the message to be sent to all tasks currently waiting for messages. The message is not copied; a reference count is maintained instead so that the message will remain valid until the last receiver releases its own reference using `rt_queue_free()`, after which the message space will be returned to the queue's internal pool.

Returns:

Upon success, this service returns the number of receivers which got awoken as a result of the operation. If zero is returned, no task was waiting on the receiving side of the queue, and the message has been enqueued. Upon error, one of the following error codes is returned:

- `-EINVAL` is returned if *q* is not a message queue descriptor, or *mbuf* is not a valid message buffer obtained from a previous call to `rt_queue_alloc()`.
- `-EIDRM` is returned if *q* is a deleted queue descriptor.
- `-ENOMEM` is returned if queuing the message would exceed the limit defined for the queue at creation.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.10.2.10 `int rt_queue_unbind (RT_QUEUE * q)`

Unbind from a shared message queue.

This user-space only service unbinds the calling task from the message queue object previously retrieved by a call to `rt_queue_bind()`.

Unbinding from a message queue when it is no more needed is especially important in order to properly release the mapping resources used to attach the shared queue memory to the caller's address space.

Parameters:

q The address of a queue descriptor to unbind from.

Returns:

0 is returned upon success. Otherwise:

- `-EINVAL` is returned if *q* is invalid or not bound.

This service can be called from:

- User-space task.

Rescheduling: never.

4.10.2.11 `int rt_queue_write (RT_QUEUE * q, const void * buf, size_t size, int mode)`

Write a message to a queue.

This service writes a complete message to a given queue. This service differs from `rt_queue_send()` in that it accepts a pointer to the raw data to be sent, instead of a canned message buffer.

Parameters:

q The descriptor address of the message queue to write to.

buf The address of the message data to be written to the queue. A message buffer will be allocated internally to convey the data.

size The size in bytes of the message data. Zero is a valid value, in which case an empty message will be sent.

mode A set of flags affecting the operation:

- `Q_URGENT` causes the message to be prepended to the message queue, ensuring a LIFO ordering.
- `Q_NORMAL` causes the message to be appended to the message queue, ensuring a FIFO ordering.
- `Q_BROADCAST` causes the message to be sent to all tasks currently waiting for messages. The message is not copied; a reference count is maintained instead so that the message will remain valid until all receivers get a copy of the message, after which the message space will be returned to the queue's internal pool.

Returns:

Upon success, this service returns the number of receivers which got awoken as a result of the operation. If zero is returned, no task was waiting on the receiving side of the queue, and the message has been enqueued. Upon error, one of the following error codes is returned:

- -EINVAL is returned if q is not a message queue descriptor.
- -EIDRM is returned if q is a deleted queue descriptor.
- -ENOMEM is returned if queuing the message would exceed the limit defined for the queue at creation, or if no memory can be obtained to convey the message data internally.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.11 Counting semaphore services.

Collaboration diagram for Counting semaphore services.:



4.11.1 Detailed Description

A counting semaphore is a synchronization object granting Xenomai tasks a concurrent access to a given number of resources maintained in an internal counter variable. The semaphore is used through the P ("Proberen", from the Dutch "test and decrement") and V ("Verhogen", increment) operations. The P operation waits for a unit to become available from the count, and the V operation releases a resource by incrementing the unit count by one.

If no more than a single resource is made available at any point in time, the semaphore enforces mutual exclusion and thus can be used to serialize access to a critical section. However, mutexes should be used instead in order to prevent priority inversions.

Files

- file [sem.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_sem_create](#) (RT_SEM *sem, const char *name, unsigned long icount, int mode)
- int [rt_sem_delete](#) (RT_SEM *sem)
- int [rt_sem_p](#) (RT_SEM *sem, RTIME timeout)
- int [rt_sem_v](#) (RT_SEM *sem)
- int [rt_sem_broadcast](#) (RT_SEM *sem)
- int [rt_sem_inquire](#) (RT_SEM *sem, RT_SEM_INFO *info)
- int [rt_sem_bind](#) (RT_SEM *sem, const char *name, RTIME timeout)
- static int [rt_sem_unbind](#) (RT_SEM *sem)

4.11.2 Function Documentation

4.11.2.1 int [rt_sem_bind](#) (RT_SEM * sem, const char * name, RTIME timeout)

Bind to a semaphore.

This user-space only service retrieves the uniform descriptor of a given Xenomai semaphore identified by its symbolic name. If the semaphore does not exist on entry, this service blocks the caller until a semaphore of the given name is created.

Parameters:

name A valid NULL-terminated name which identifies the semaphore to bind to.

sem The address of a semaphore descriptor retrieved by the operation. Contents of this memory is undefined upon failure.

timeout The number of clock ticks to wait for the registration to occur (see note). Passing TM_INFINITE causes the caller to block indefinitely until the object is registered. Passing TM_NONBLOCK causes the service to return immediately without waiting if the object is not registered on entry.

Returns:

0 is returned upon success. Otherwise:

- -EFAULT is returned if *sem* or *name* is referencing invalid memory.
- -EINTR is returned if `rt_task_unblock()` has been called for the waiting task before the retrieval has completed.
- -EWOULDBLOCK is returned if *timeout* is equal to TM_NONBLOCK and the searched object is not registered on entry.
- -ETIMEDOUT is returned if the object cannot be retrieved within the specified amount of time.
- -EPERM is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.11.2.2 int rt_sem_broadcast (RT_SEM * sem)

Broadcast a semaphore.

Unblock all tasks waiting on a semaphore. Awaken tasks return from `rt_sem_p()` as if the semaphore has been signaled. The semaphore count is zeroed as a result of the operation.

Parameters:

sem The descriptor address of the affected semaphore.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *sem* is not a semaphore descriptor.
- -EIDRM is returned if *sem* is a deleted semaphore descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.11.2.3 `int rt_sem_create (RT_SEM * sem, const char * name, unsigned long icount, int mode)`

Create a counting semaphore.

Parameters:

sem The address of a semaphore descriptor Xenomai will use to store the semaphore-related data. This descriptor must always be valid while the semaphore is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the semaphore. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created semaphore.

icount The initial value of the semaphore count.

mode The semaphore creation mode. The following flags can be OR'ed into this bitmask, each of them affecting the new semaphore:

- S_FIFO makes tasks pend in FIFO order on the semaphore.
- S_PRIO makes tasks pend in priority order on the semaphore.
- S_PULSE causes the semaphore to behave in "pulse" mode. In this mode, the V (signal) operation attempts to release a single waiter each time it is called, but without incrementing the semaphore count if no waiter is pending. For this reason, the semaphore count in pulse mode remains zero.

Returns:

0 is returned upon success. Otherwise:

- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to register the semaphore.
- -EEXIST is returned if the *name* is already in use by some registered object.

- -EINVAL is returned if the *icount* is non-zero and *mode* specifies a pulse semaphore.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.11.2.4 `int rt_sem_delete (RT_SEM * sem)`

Delete a semaphore.

Destroy a semaphore and release all the tasks currently pending on it. A semaphore exists in the system since `rt_sem_create()` has been called to create it, so this service must be called in order to destroy it afterwards.

Parameters:

sem The descriptor address of the affected semaphore.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *sem* is not a semaphore descriptor.
- -EIDRM is returned if *sem* is a deleted semaphore descriptor.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.11.2.5 `int rt_sem_inquire (RT_SEM * sem, RT_SEM_INFO * info)`

Inquire about a semaphore.

Return various information about the status of a given semaphore.

Parameters:

sem The descriptor address of the inquired semaphore.

info The address of a structure the semaphore information will be written to.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success. Otherwise:

- -EINVAL is returned if *sem* is not a semaphore descriptor.
- -EIDRM is returned if *sem* is a deleted semaphore descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.11.2.6 `int rt_sem_p (RT_SEM * sem, RTIME timeout)`

Pend on a semaphore.

Acquire a semaphore unit. If the semaphore value is greater than zero, it is decremented by one and the service immediately returns to the caller. Otherwise, the caller is blocked until the semaphore is either signaled or destroyed, unless a non-blocking operation has been required.

Parameters:

sem The descriptor address of the affected semaphore.

timeout The number of clock ticks to wait for a semaphore unit to be available (see note).
Passing TM_INFINITE causes the caller to block indefinitely until a unit is available.
Passing TM_NONBLOCK causes the service to return immediately without waiting if no unit is available.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *sem* is not a semaphore descriptor.

- -EIDRM is returned if *sem* is a deleted semaphore descriptor, including if the deletion occurred while the caller was sleeping on it for a unit to become available.
- -EWOULDBLOCK is returned if *timeout* is equal to TM_NONBLOCK and the semaphore value is zero.
- -EINTR is returned if `rt_task_unblock()` has been called for the waiting task before a semaphore unit has become available.
- -ETIMEDOUT is returned if no unit is available within the specified amount of time.
- -EPERM is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *timeout* is equal to TM_NONBLOCK.
- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.11.2.7 `int rt_sem_unbind (RT_SEM * sem) [inline, static]`

Unbind from a semaphore.

This user-space only service unbinds the calling task from the semaphore object previously retrieved by a call to `rt_sem_bind()`.

Parameters:

sem The address of a semaphore descriptor to unbind from.

Returns:

0 is always returned.

This service can be called from:

- User-space task.

Rescheduling: never.

4.11.2.8 `int rt_sem_v (RT_SEM * sem)`

Signal a semaphore.

Release a semaphore unit. If the semaphore is pended, the first waiting task (by queuing order) is immediately unblocked; otherwise, the semaphore value is incremented by one.

Parameters:

sem The descriptor address of the affected semaphore.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *sem* is not a semaphore descriptor.
- -EIDRM is returned if *sem* is a deleted semaphore descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.12 Task management services.

Collaboration diagram for Task management services.:



4.12.1 Detailed Description

Xenomai provides a set of multitasking mechanisms. The basic process object performing actions in Xenomai is a task, a logically complete path of application code. Each Xenomai task is an independent portion of the overall application code embodied in a C procedure, which executes on its own stack context.

The Xenomai scheduler ensures that concurrent tasks are run according to one of the supported scheduling policies. Currently, the Xenomai scheduler supports fixed priority-based FIFO and round-robin policies.

Files

- file [task.c](#)

This file is part of the Xenomai project.

Functions

- int [rt_task_create](#) (RT_TASK *task, const char *name, int stksize, int prio, int mode)
- int [rt_task_start](#) (RT_TASK *task, void(*entry)(void *cookie), void *cookie)
- int [rt_task_suspend](#) (RT_TASK *task)
- int [rt_task_resume](#) (RT_TASK *task)
- int [rt_task_delete](#) (RT_TASK *task)
- int [rt_task_yield](#) (void)
- int [rt_task_set_periodic](#) (RT_TASK *task, RTIME idate, RTIME period)
- int [rt_task_wait_period](#) (unsigned long *overruns_r)
- int [rt_task_set_priority](#) (RT_TASK *task, int prio)
- int [rt_task_sleep](#) (RTIME delay)
- int [rt_task_sleep_until](#) (RTIME date)
- int [rt_task_unblock](#) (RT_TASK *task)
- int [rt_task_inquire](#) (RT_TASK *task, RT_TASK_INFO *info)
- int [rt_task_add_hook](#) (int type, void(*routine)(void *cookie))
- int [rt_task_remove_hook](#) (int type, void(*routine)(void *cookie))
- int [rt_task_catch](#) (void(*handler)(rt_sigset_t))
- int [rt_task_notify](#) (RT_TASK *task, rt_sigset_t signals)
- int [rt_task_set_mode](#) (int clrmask, int setmask, int *mode_r)
- RT_TASK * [rt_task_self](#) (void)
- int [rt_task_slice](#) (RT_TASK *task, RTIME quantum)
- ssize_t [rt_task_send](#) (RT_TASK *task, RT_TASK_MCB *mcb_s, RT_TASK_MCB *mcb_r, RTIME timeout)
- int [rt_task_receive](#) (RT_TASK_MCB *mcb_r, RTIME timeout)

- int `rt_task_reply` (int flowid, `RT_TASK_MCB *mcb_s`)
- static int `rt_task_spawn` (`RT_TASK *task`, const char *name, int stksize, int prio, int mode, void(*entry)(void *cookie), void *cookie)
- int `rt_task_shadow` (`RT_TASK *task`, const char *name, int prio, int mode)
- int `rt_task_bind` (`RT_TASK *task`, const char *name, RTIME timeout)
- static int `rt_task_unbind` (`RT_TASK *task`)
- int `rt_task_join` (`RT_TASK *task`)

4.12.2 Function Documentation

4.12.2.1 int `rt_task_add_hook` (int *type*, void(*)*(void *cookie) routine*)

Install a task hook.

The real-time kernel allows to register user-defined routines which get called whenever a specific scheduling event occurs. Multiple hooks can be chained for a single event type, and get called on a FIFO basis.

The scheduling is locked while a hook is executing.

Parameters:

type Defines the kind of hook to install:

- `T_HOOK_START`: The user-defined routine will be called on behalf of the starter task whenever a new task starts. An opaque cookie is passed to the routine which can use it to retrieve the descriptor address of the started task through the `T_DESC()` macro.
- `T_HOOK_DELETE`: The user-defined routine will be called on behalf of the deleter task whenever a task is deleted. An opaque cookie is passed to the routine which can use it to retrieve the descriptor address of the deleted task through the `T_DESC()` macro.
- `T_HOOK_SWITCH`: The user-defined routine will be called on behalf of the resuming task whenever a context switch takes place. An opaque cookie is passed to the routine which can use it to retrieve the descriptor address of the task which has been switched in through the `T_DESC()` macro.

Parameters:

routine The address of the user-supplied routine to call.

Returns:

0 is returned upon success. Otherwise, one of the following error codes indicates the cause of the failure:

- `-EINVAL` is returned if *type* is incorrect.
- `-ENOMEM` is returned if not enough memory is available from the system heap to add the new hook.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task

Rescheduling: never.

4.12.2.2 `int rt_task_bind (RT_TASK * task, const char * name, RTIME timeout)`

Bind to a real-time task.

This user-space only service retrieves the uniform descriptor of a given Xenomai task identified by its symbolic name. If the task does not exist on entry, this service blocks the caller until a task of the given name is created.

Parameters:

name A valid NULL-terminated name which identifies the task to bind to.

task The address of a task descriptor retrieved by the operation. Contents of this memory is undefined upon failure.

timeout The number of clock ticks to wait for the registration to occur (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until the object is registered. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if the object is not registered on entry.

Returns:

0 is returned upon success. Otherwise:

- `-EFAULT` is returned if *task* or *name* is referencing invalid memory.
- `-EINTR` is returned if `rt_task_unblock()` has been called for the waiting task before the retrieval has completed.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and the searched object is not registered on entry.
- `-ETIMEDOUT` is returned if the object cannot be retrieved within the specified amount of time.
- `-EPERM` is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- User-space task (switches to primary mode)

Rescheduling: always unless the request is immediately satisfied or *timeout* specifies a non-blocking operation.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.12.2.3 `int rt_task_catch (void(*) (rt_sigset_t) handler)`

Install a signal handler.

This service installs a signal handler for the current task. Signals are discrete events tasks can receive each time they resume execution. When signals are pending upon resumption, *handler* is fired to process them. Signals can be sent using `rt_task_notify()`. A task can block the signal delivery by passing the `T_NOSIG` bit to `rt_task_set_mode()`.

Calling this service implicitly unblocks the signal delivery for the caller.

Parameters:

handler The address of the user-supplied routine to fire when signals are pending for the task. This handler is passed the set of pending signals as its first and only argument.

Returns:

0 upon success, or:

- `-EPERM` is returned if this service was not called from a real-time task context.

Environments:

This service can be called from:

- Kernel-based task

Rescheduling: possible.

4.12.2.4 `int rt_task_create (RT_TASK * task, const char * name, int stksize, int prio, int mode)`

Create a new real-time task.

Creates a real-time task, either running in a kernel module or in user-space depending on the caller's context.

Parameters:

task The address of a task descriptor Xenomai will use to store the task-related data. This descriptor must always be valid while the task is active therefore it must be allocated in permanent memory.

The task is left in an innocuous state until it is actually started by `rt_task_start()`.

Parameters:

name An ASCII string standing for the symbolic name of the task. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created task.

stacksize The size of the stack (in bytes) for the new task. If zero is passed, a reasonable pre-defined size will be substituted.

prio The base priority of the new task. This value must range from [1 .. 99] (inclusive) where 1 is the lowest effective priority.

mode The task creation mode. The following flags can be OR'ed into this bitmask, each of them affecting the new task:

- T_FPU allows the task to use the FPU whenever available on the platform. This flag is forced for user-space tasks.
- T_SUSP causes the task to start in suspended mode. In such a case, the thread will have to be explicitly resumed using the `rt_task_resume()` service for its execution to actually begin.
- T_CPU(cpuid) makes the new task affine to CPU # **cpuid**. CPU identifiers range from 0 to RTHAL_NR_CPUS - 1 (inclusive).
- T_JOINABLE (user-space only) allows another task to wait on the termination of the new task. This implies that `rt_task_join()` is actually called for this task to clean up any user-space located resources after its termination.

Passing T_FPU|T_CPU(1) in the *mode* parameter thus creates a task with FPU support enabled and which will be affine to CPU #1.

Returns:

0 is returned upon success. Otherwise:

- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to create or register the task.
- -EEXIST is returned if the *name* is already in use by some registered object.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.12.2.5 int `rt_task_delete` (RT_TASK * *task*)

Delete a real-time task.

Terminate a task and release all the real-time kernel resources it currently holds. A task exists in the system since `rt_task_create()` has been called to create it, so this service must be called in order to destroy it afterwards.

Native tasks implement a mechanism by which they are immune from deletion by other tasks while they run into a deemed safe section of code. This feature is used internally by the native skin in order to prevent tasks from being deleted in the middle of a critical section, without resorting to interrupt masking when the latter is not an option. For this reason, the caller of `rt_task_delete()` might be blocked and a rescheduling take place, waiting for the target task to exit such critical section.

The DELETE hooks are called on behalf of the calling context (if any). The information stored in the task control block remains valid until all hooks have been called.

Parameters:

task The descriptor address of the affected task. If *task* is NULL, the current task is deleted.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor.
- -EPERM is returned if *task* is NULL but not called from a task context, or this service was called from an asynchronous context.
- -EINTR is returned if `rt_task_unblock()` has been invoked for the caller while it was waiting for *task* to exit a safe section. In such a case, the deletion process has been aborted and *task* remains unaffected.
- -EIDRM is returned if *task* is a deleted task descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code only if *task* is non-NULL.
- Kernel-based task
- Any user-space context (conforming call)

Rescheduling: always if *task* is NULL, and possible if the deleted task is currently running into a safe section.

4.12.2.6 int rt_task_inquire (RT_TASK * task, RT_TASK_INFO * info)

Inquire about a real-time task.

Return various information about the status of a given task.

Parameters:

task The descriptor address of the inquired task. If *task* is NULL, the current task is inquired.

info The address of a structure the task information will be written to.

Returns:

0 is returned and status information is written to the structure pointed at by *info* upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor.
- -EPERM is returned if *task* is NULL but not called from a task context.
- -EIDRM is returned if *task* is a deleted task descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *task* is non-NULL.
- Kernel-based task
- User-space task

Rescheduling: never.

4.12.2.7 int rt_task_join (RT_TASK * task)

Wait on the termination of a real-time task.

This user-space only service blocks the caller in non-real-time context until *task* has terminated. Note that the specified task must have been created with the T_JOINABLE mode flag set.

Parameters:

task The address of a task descriptor to join.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if the task was not created with T_JOINABLE set or some other task is already waiting on the termination.
- -EDEADLK is returned if *task* refers to the caller.

This service can be called from:

- User-space task.

Rescheduling: always unless the task was already terminated.

4.12.2.8 `int rt_task_notify (RT_TASK * task, rt_sigset_t signals)`

Send signals to a task.

This service sends a set of signals to a given task. A task can install a signal handler using the [rt_task_catch\(\)](#) service to process them.

Parameters:

task The descriptor address of the affected task which must have been previously created by the [rt_task_create\(\)](#) service.

signals The set of signals to make pending for the task. This set is OR'ed with the current set of pending signals for the task; there is no count of occurrence maintained for each available signal, which is either pending or cleared.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor.
- -EPERM is returned if *task* is NULL but not called from a real-time task context.
- -EIDRM is returned if *task* is a deleted task descriptor.
- -ESRCH is returned if *task* has not set any signal handler.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *task* is non-NULL.
- Kernel-based task
- User-space task

Rescheduling: possible.

4.12.2.9 `int rt_task_receive (RT_TASK_MCB * mcb_r, RTIME timeout)`

Receive a message from a task.

This service is part of the synchronous message passing support available to Xenomai tasks. It allows the caller to receive a variable-sized message sent from another task using the [rt_task_send\(\)](#) service. The sending task is blocked until the caller invokes [rt_task_reply\(\)](#) to finish the transaction.

A basic message control block is used to store the location and size of the data area to receive from the client, in addition to a user-defined operation code.

Parameters:

mcb_r The address of a message control block referring to the receive message area. The fields from this control block should be set as follows:

- *mcb_r->data* should contain the address of a buffer large enough to collect the data sent by the remote task;
- *mcb_r->size* should contain the size in bytes of the buffer space pointed at by *mcb_r->data*. If *mcb_r->size* is lower than the actual size of the received message, no data copy takes place and `-ENOBUFS` is returned to the caller. See note.

Upon return, *mcb_r->opcode* will contain the operation code sent from the remote task using [rt_task_send\(\)](#).

Parameters:

timeout The number of clock ticks to wait for receiving a message (see note). Passing `TM_INFINITE` causes the caller to block indefinitely until a remote task eventually sends a message. Passing `TM_NONBLOCK` causes the service to return immediately without waiting if no remote task is currently waiting for sending a message.

Returns:

A strictly positive value is returned upon success, representing a flow identifier for the opening transaction; this token should be passed to [rt_task_reply\(\)](#), in order to send back a reply to and unblock the remote task appropriately. Otherwise:

- `-ENOBUFS` is returned if *mcb_r* does not point at a message area large enough to collect the remote task's message.
- `-EWOULDBLOCK` is returned if *timeout* is equal to `TM_NONBLOCK` and no remote task is currently waiting for sending a message to the caller.
- `-ETIMEDOUT` is returned if no message was received within the *timeout*.
- `-EINTR` is returned if [rt_task_unblock\(\)](#) has been called for the caller before any message was available.
- `-EPERM` is returned if this service was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: Always.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds. When called from a user-space task, this service may need to allocate some temporary buffer space from the system heap to hold the received data if the size of the latter exceeds a certain amount; the threshold before allocation is currently set to 64 bytes.

4.12.2.10 `int rt_task_remove_hook (int type, void(*)(void *cookie) routine)`

Remove a task hook.

This service allows to remove a task hook previously registered using [rt_task_add_hook\(\)](#).

Parameters:

type Defines the kind of hook to uninstall. Possible values are:

- `T_HOOK_START`
- `T_HOOK_DELETE`
- `T_HOOK_SWITCH`

Parameters:

routine The address of the user-supplied routine to remove from the hook list.

Returns:

0 is returned upon success. Otherwise, one of the following error codes indicates the cause of the failure:

- `-EINVAL` is returned if *type* is incorrect.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task

Rescheduling: never.

4.12.2.11 `int rt_task_reply (int flowid, RT_TASK_MCB * mcb_s)`

Reply to a task.

This service is part of the synchronous message passing support available to Xenomai tasks. It allows the caller to send back a variable-sized message to the client task, once the initial message

from this task has been pulled using `rt_task_receive()` and processed. As a consequence of this call, the remote task will be unblocked from the `rt_task_send()` service.

A basic message control block is used to store the location and size of the data area to send back, in addition to a user-defined status code.

Parameters:

flowid The flow identifier returned by a previous call to `rt_task_receive()` which uniquely identifies the current transaction.

mcb_s The address of an optional message control block referring to the message to be sent back. If *mcb_s* is NULL, the client will be unblocked without getting any reply data. When *mcb_s* is valid, the fields from this control block should be set as follows:

- *mcb_s->data* should contain the address of the payload data to send to the remote task.
- *mcb_s->size* should contain the size in bytes of the payload data pointed at by *mcb_s->data*. 0 is a legitimate value, and indicates that no payload data will be transferred. In the latter case, *mcb_s->data* will be ignored. See note.
- *mcb_s->opcode* is an opaque status code carried during the message transfer the caller can fill with any appropriate value. It will be made available "as is" to the remote task into the status code field by the `rt_task_send()` service. If *mcb_s* is NULL, 0 will be returned to the client into the status code field.

Returns:

0 is returned upon success. Otherwise:

- -ENXIO is returned if *flowid* does not match the expected identifier returned from the latest call of the current task to `rt_task_receive()`, or if the remote task stopped waiting for the reply in the meantime (e.g. the client could have been deleted or forcibly unblocked).
- -EPERM is returned if this service was called from an invalid context (e.g. interrupt, or non-primary).

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: Always.

Note:

When called from a user-space task, this service may need to allocate some temporary buffer space from the system heap to hold the reply data if the size of the latter exceeds a certain amount; the threshold before allocation is currently set to 64 bytes.

4.12.2.12 `int rt_task_resume (RT_TASK * task)`

Resume a real-time task.

Forcibly resume the execution of a task which has been previously suspended by a call to `rt_task_suspend()`.

The suspension nesting count is decremented so that `rt_task_resume()` will only resume the task if this count falls down to zero as a result of the current invocation.

Parameters:

task The descriptor address of the affected task.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor.
- -EIDRM is returned if *task* is a deleted task descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible if the suspension nesting level falls down to zero as a result of the current invocation.

4.12.2.13 `RT_TASK* rt_task_self (void)`

Retrieve the current task.

Return the current task descriptor address.

Returns:

The address of the caller's task descriptor is returned upon success, or NULL if the calling context is asynchronous (i.e. not a Xenomai task).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine Those will cause a NULL return.
- Kernel-based task
- User-space task

Rescheduling: never.

4.12.2.14 `ssize_t rt_task_send (RT_TASK * task, RT_TASK_MCB * mcb_s, RT_TASK_MCB * mcb_r, RTIME timeout)`

Send a message to a task.

This service is part of the synchronous message passing support available to Xenomai tasks. It allows the caller to send a variable-sized message to another task, waiting for the remote to receive the initial message by a call to `rt_task_receive()`, then reply to it using `rt_task_reply()`.

A basic message control block is used to store the location and size of the data area to send or retrieve upon reply, in addition to a user-defined operation code.

Parameters:

task The descriptor address of the recipient task.

mcb_s The address of the message control block referring to the message to be sent. The fields from this control block should be set as follows:

- *mcb_s->data* should contain the address of the payload data to send to the remote task.
- *mcb_s->size* should contain the size in bytes of the payload data pointed at by *mcb_s->data*. 0 is a legitimate value, and indicates that no payload data will be transferred. In the latter case, *mcb_s->data* will be ignored. See note.
- *mcb_s->opcode* is an opaque operation code carried during the message transfer the caller can fill with any appropriate value. It will be made available "as is" to the remote task into the operation code field by the `rt_task_receive()` service.

Parameters:

mcb_r The address of an optional message control block referring to the reply message area. If *mcb_r* is NULL and a reply is sent back by the remote task, the reply message will be discarded, and -ENOBUFS will be returned to the caller. When *mcb_r* is valid, the fields from this control block should be set as follows:

- *mcb_r->data* should contain the address of a buffer large enough to collect the reply data from the remote task.
- *mcb_r->size* should contain the size in bytes of the buffer space pointed at by *mcb_r->data*. If *mcb_r->size* is lower than the actual size of the reply message, no data copy takes place and -ENOBUFS is returned to the caller. See note.

Upon return, *mcb_r->opcode* will contain the status code sent back from the remote task using `rt_task_reply()`, or 0 if unspecified.

Parameters:

timeout The number of clock ticks to wait for the remote task to reply to the initial message (see note). Passing TM_INFINITE causes the caller to block indefinitely until the remote task eventually replies. Passing TM_NONBLOCK causes the service to return immediately without waiting if the remote task is not waiting for messages (i.e. if *task* is not currently blocked on the `rt_task_receive()` service).

Returns:

A positive value is returned upon success, representing the length (in bytes) of the reply message returned by the remote task. 0 is a success status, meaning either that *mcb_r* was NULL on entry, or that no actual message was passed to the remote call to [rt_task_reply\(\)](#). Otherwise:

- -ENOBUFS is returned if *mcb_r* does not point at a message area large enough to collect the remote task's reply. This includes the case where *mcb_r* is NULL on entry albeit the remote task attempts to send a reply message.
- -EWOULDBLOCK is returned if *timeout* is equal to TM_NONBLOCK and *task* is not currently blocked on the [rt_task_receive\(\)](#) service.
- -EIDRM is returned if *task* has been deleted while waiting for a reply.
- -EINTR is returned if [rt_task_unblock\(\)](#) has been called for the caller before any reply was available.
- -EPERM is returned if this service should block, but was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: Always.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds. When called from a user-space task, this service may need to allocate some temporary buffer space from the system heap to hold both the sent and the reply data if this cumulated size exceeds a certain amount; the threshold before allocation is currently set to 64 bytes.

4.12.2.15 int rt_task_set_mode (int clrmask, int setmask, int * mode_r)

Change task mode bits.

Each Xenomai task has a set of internal bits determining various operating conditions; the [rt_task_set_mode\(\)](#) service allows to alter three of them, respectively controlling:

- whether the task locks the rescheduling procedure,
- whether the task undergoes a round-robin scheduling,
- whether the task blocks the delivery of signals.

To this end, `rt_task_set_mode()` takes a bitmask of mode bits to clear for disabling the corresponding modes, and another one to set for enabling them. The mode bits which were previously in effect can be returned upon request.

The following bits can be part of the bitmask:

- `T_LOCK` causes the current task to lock the scheduler. Clearing this bit unlocks the scheduler.
- `T_RRB` causes the current task to be marked as undergoing the round-robin scheduling policy. If the task is already undergoing the round-robin scheduling policy at the time this service is called, the time quantum remains unchanged.
- `T_NOSIG` disables the asynchronous signal delivery for the current task.
- `T_SHIELD` enables the interrupt shield for the current user-space task. When engaged, the interrupt shield protects the Xenomai task running in secondary mode from any preemption by the regular Linux interrupt handlers, without delaying in any way the Xenomai interrupt handling. The shield is operated on a per-task basis at each context switch, depending on the setting of this flag. This flag is cleared by default for new user-space tasks. This feature is only available if the `CONFIG_XENO_OPT_ISHIELD` option has been enabled at configuration time; otherwise, this flag is simply ignored.
- When set, `T_WARNSW` causes the `SIGXCPU` signal to be sent to the current user-space task whenever it switches to the secondary mode. This feature is useful to detect unwanted migrations to the Linux domain.
- `T_RPIOFF` disables thread priority coupling between Xenomai and Linux schedulers. This bit prevents the root Linux thread from inheriting the priority of the running shadow Xenomai thread. Use `CONFIG_XENO_OPT_RPIOFF` to globally disable priority coupling.
- `T_PRIMARY` can be passed to switch the current user-space task to primary mode (`setmask |= T_PRIMARY`), or secondary mode (`clrmask |= T_PRIMARY`). Upon return from `rt_task_set_mode()`, the user-space task will run into the specified domain.

Normally, this service can only be called on behalf of a regular real-time task, either running in kernel or user-space. However, as a special exception, requests for setting/clearing the `T_LOCK` bit from asynchronous contexts are silently dropped, and the call returns successfully if no other mode bits have been specified. This is consistent with the fact that Xenomai enforces a scheduler lock until the outer interrupt handler has returned.

Parameters:

clrmask A bitmask of mode bits to clear for the current task, before *setmask* is applied. 0 is an acceptable value which leads to a no-op.

setmask A bitmask of mode bits to set for the current task. 0 is an acceptable value which leads to a no-op.

mode_r If non-NULL, *mode_r* must be a pointer to a memory location which will be written upon success with the previous set of active mode bits. If NULL, the previous set of active mode bits will not be returned.

Returns:

0 is returned upon success, or:

- -EINVAL if either *setmask* or *clrmask* specifies invalid bits. T_PRIMARY is invalid for kernel-based tasks.
- -EPERM is returned if this service was not called from a real-time task context.

Environments:

This service can be called from:

- Kernel-based task
- User-space task

Rescheduling: possible, if T_LOCK has been passed into *clrmask* and the calling context is a task.

4.12.2.16 `int rt_task_set_periodic (RT_TASK * task, RTIME idate, RTIME period)`

Make a real-time task periodic.

Make a task periodic by programming its first release point and its period in the processor time line. Subsequent calls to `rt_task_wait_period()` will delay the task until the next periodic release point in the processor timeline is reached.

Parameters:

task The descriptor address of the affected task. This task is immediately delayed until the first periodic release point is reached. If *task* is NULL, the current task is set periodic.

idate The initial (absolute) date of the first release point, expressed in clock ticks (see note). The affected task will be delayed until this point is reached. If *idate* is equal to TM_NOW, the current system date is used, and no initial delay takes place.

period The period of the task, expressed in clock ticks (see note). Passing TM_INFINITE attempts to stop the task's periodic timer; in the latter case, the routine always exits successfully, regardless of the previous state of this timer.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor, or *period* is different from TM_INFINITE but shorter than the scheduling latency value for the target system, as available from `/proc/xenomai/latency`.
- -EIDRM is returned if *task* is a deleted task descriptor.
- -ETIMEDOUT is returned if *idate* is different from TM_INFINITE and represents a date in the past.
- -EWOULDBLOCK is returned if the system timer is not active.
- -EPERM is returned if *task* is NULL but not called from a task context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code or interrupt only if *task* is non-NULL.
- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always if the operation affects the current task and *idate* has not elapsed yet.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.12.2.17 `int rt_task_set_priority(RT_TASK * task, int prio)`

Change the base priority of a real-time task.

Changing the base priority of a task does not affect the priority boost the target task might have obtained as a consequence of a previous priority inheritance.

Parameters:

task The descriptor address of the affected task.

prio The new task priority. This value must range from [1 .. 99] (inclusive) where 1 is the lowest effective priority.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor, or if *prio* is invalid.
- -EPERM is returned if *task* is NULL but not called from a task context.
- -EIDRM is returned if *task* is a deleted task descriptor.

Side-effects:

- This service calls the rescheduling procedure.
- Assigning the same priority to a running or ready task moves it to the end of its priority group, thus causing a manual round-robin.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code

- Interrupt service routine only if *task* is non-NULL.
- Kernel-based task
- User-space task

Rescheduling: possible if *task* is the current one.

4.12.2.18 `int rt_task_shadow (RT_TASK * task, const char * name, int prio, int mode)`

Turns the current Linux task into a native Xenomai task.

Creates a real-time task running in the context of the calling regular Linux task in user-space.

Parameters:

task The address of a task descriptor Xenomai will use to store the task-related data. This descriptor must always be valid while the task is active therefore it must be allocated in permanent memory.

The current context is switched to primary execution mode and returns immediately, unless T_SUSP has been passed in the *mode* parameter.

Parameters:

name An ASCII string standing for the symbolic name of the task. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created task.

prio The base priority which will be set for the current task. This value must range from [1 .. 99] (inclusive) where 1 is the lowest effective priority.

mode The task creation mode. The following flags can be OR'ed into this bitmask, each of them affecting the new task:

- T_FPU allows the task to use the FPU whenever available on the platform. This flag is forced for this call, therefore it can be omitted.
- T_SUSP causes the task to enter the suspended mode after it has been put under Xenomai's control. In such a case, a call to `rt_task_resume()` will be needed to wake up the current task.
- T_CPU(*cpuid*) makes the current task affine to CPU # **cpuid**. CPU identifiers range from 0 to RTHAL_NR_CPUS - 1 (inclusive). The calling task will migrate to another processor before this service returns if the current one is not part of the CPU affinity mask.

Passing T_CPU(0)|T_CPU(1) in the *mode* parameter thus defines a task affine to CPUs #0 and #1.

Returns:

0 is returned upon success. Otherwise:

- -EBUSY is returned if the current Linux task is already mapped to a Xenomai context.
- -ENOMEM is returned if the system fails to get enough dynamic memory from the global real-time heap in order to create or register the task.

- -EEXIST is returned if the *name* is already in use by some registered object.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- User-space task (enters primary mode)

Rescheduling: possible.

4.12.2.19 `int rt_task_sleep (RTIME delay)`

Delay the calling task (relative).

Delay the execution of the calling task for a number of internal clock ticks.

Parameters:

delay The number of clock ticks to wait before resuming the task (see note). Passing zero causes the task to return immediately with no delay.

Returns:

0 is returned upon success, otherwise:

- -EINTR is returned if `rt_task_unblock()` has been called for the sleeping task before the sleep time has elapsed.
- -EWOULDBLOCK is returned if the system timer is inactive.
- -EPERM is returned if this service was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless a null delay is given.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.12.2.20 `int rt_task_sleep_until (RTIME date)`

Delay the calling task (absolute).

Delay the execution of the calling task until a given date is reached.

Parameters:

date The absolute date in clock ticks to wait before resuming the task (see note). Passing an already elapsed date causes the task to return immediately with no delay.

Returns:

0 is returned upon success. Otherwise:

- -EINTR is returned if `rt_task_unblock()` has been called for the sleeping task before the sleep time has elapsed.
- -ETIMEDOUT is returned if *date* has already elapsed.
- -EWOULDBLOCK is returned if the system timer is inactive.
- -EPERM is returned if this service was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always unless a date in the past is given.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.12.2.21 `int rt_task_slice (RT_TASK * task, RTIME quantum)`

Set a task's round-robin quantum.

Set the time credit allotted to a task undergoing the round-robin scheduling. As a side-effect, `rt_task_slice()` refills the current quantum of the target task.

Parameters:

task The descriptor address of the affected task. If *task* is NULL, the current task is considered.

quantum The round-robin quantum for the task expressed in clock ticks (see note).

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor, or if *quantum* is zero.
- -EPERM is returned if *task* is NULL but not called from a task context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *task* is non-NULL.
- Kernel-based task
- User-space task

Rescheduling: never.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the CONFIG_XENO_OPT_TIMING_PERIOD parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.12.22 `int rt_task_spawn (RT_TASK * task, const char * name, int stksize, int prio, int mode, void(*)(void *cookie) entry, void * cookie) [inline, static]`

Spawn a new real-time task.

Creates and immediately starts a real-time task, either running in a kernel module or in user-space depending on the caller's context. This service is a simple shorthand for `rt_task_create()` followed by a call to `rt_task_start()`.

Parameters:

task The address of a task descriptor Xenomai will use to store the task-related data. This descriptor must always be valid while the task is active therefore it must be allocated in permanent memory.

name An ASCII string standing for the symbolic name of the task. When non-NULL and non-empty, this string is copied to a safe place into the descriptor, and passed to the registry package if enabled for indexing the created task.

stksize The size of the stack (in bytes) for the new task. If zero is passed, a reasonable pre-defined size will be substituted.

prio The base priority of the new task. This value must range from [1 .. 99] (inclusive) where 1 is the lowest effective priority.

mode The task creation mode. The following flags can be OR'ed into this bitmask, each of them affecting the new task:

- `T_FPU` allows the task to use the FPU whenever available on the platform. This flag is forced for user-space tasks.
- `T_SUSP` causes the task to start in suspended mode. In such a case, the thread will have to be explicitly resumed using the `rt_task_resume()` service for its execution to actually begin.
- `T_CPU(cpuid)` makes the new task affine to CPU # `cpuid`. CPU identifiers range from 0 to `RTHAL_NR_CPUS - 1` (inclusive).
- `T_JOINABLE` (user-space only) allows another task to wait on the termination of the new task. This implies that `rt_task_join()` is actually called for this task to clean up any user-space located resources after its termination.

Passing `T_FPU|T_CPU(1)` in the *mode* parameter thus creates a task with FPU support enabled and which will be affine to CPU #1.

Parameters:

entry The address of the task's body routine. In other words, it is the task entry point.

cookie A user-defined opaque cookie the real-time kernel will pass to the emerging task as the sole argument of its entry point.

Returns:

0 is returned upon success. Otherwise:

- `-ENOMEM` is returned if the system fails to get enough dynamic memory from the global real-time heap in order to create the new task's stack space or register the task.
- `-EEXIST` is returned if the *name* is already in use by some registered object.
- `-EPERM` is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.12.2.23 int rt_task_start (RT_TASK * task, void(*) (void *cookie) entry, void * cookie)

Start a real-time task.

Start a (newly) created task, scheduling it for the first time. This call releases the target task from the dormant state.

The TSTART hooks are called on behalf of the calling context (if any, see `rt_task_add_hook()`).

Parameters:

task The descriptor address of the affected task which must have been previously created by the `rt_task_create()` service.

entry The address of the task's body routine. In other words, it is the task entry point.

cookie A user-defined opaque cookie the real-time kernel will pass to the emerging task as the sole argument of its entry point.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor.
- -EIDRM is returned if *task* is a deleted task descriptor.
- -EBUSY is returned if *task* is already started.
- -EPERM is returned if this service was called from an asynchronous context.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Kernel-based task
- User-space task

Rescheduling: possible.

4.12.2.24 int rt_task_suspend (RT_TASK * task)

Suspend a real-time task.

Forcibly suspend the execution of a task. This task will not be eligible for scheduling until it is explicitly resumed by a call to `rt_task_resume()`. In other words, the suspended state caused by a call to `rt_task_suspend()` is cumulative with respect to the delayed and blocked states caused by other services, and is managed separately from them.

A nesting count is maintained so that `rt_task_suspend()` and `rt_task_resume()` must be used in pairs.

Parameters:

task The descriptor address of the affected task. If *task* is NULL, the current task is suspended.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor.
- -EPERM is returned if the addressed *task* is not allowed to sleep (i.e. scheduler locked).

- -EIDRM is returned if *task* is a deleted task descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine only if *task* is non-NULL.
- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always if *task* is NULL.

4.12.2.25 `int rt_task_unbind (RT_TASK * task) [inline, static]`

Unbind from a real-time task.

This user-space only service unbinds the calling task from the task object previously retrieved by a call to `rt_task_bind()`.

Parameters:

task The address of a task descriptor to unbind from.

Returns:

0 is always returned.

This service can be called from:

- User-space task.

Rescheduling: never.

4.12.2.26 `int rt_task_unblock (RT_TASK * task)`

Unblock a real-time task.

Break the task out of any wait it is currently in. This call clears all delay and/or resource wait condition for the target task. However, `rt_task_unblock()` does not resume a task which has been forcibly suspended by a previous call to `rt_task_suspend()`. If all suspensive conditions are gone, the task becomes eligible anew for scheduling.

Parameters:

task The descriptor address of the affected task.

Returns:

0 is returned upon success. Otherwise:

- -EINVAL is returned if *task* is not a task descriptor.
- -EIDRM is returned if *task* is a deleted task descriptor.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: possible.

4.12.2.27 `int rt_task_wait_period (unsigned long * overruns_r)`

Wait for the next periodic release point.

Make the current task wait for the next periodic release point in the processor time line.

Parameters:

overruns_r If non-NULL, *overruns_r* must be a pointer to a memory location which will be written with the count of pending overruns. This value is copied only when `rt_task_wait_period()` returns -ETIMEDOUT or success; the memory location remains unmodified otherwise. If NULL, this count will never be copied back.

Returns:

0 is returned upon success; if *overruns_r* is valid, zero is copied to the pointed memory location. Otherwise:

- -EWOULDBLOCK is returned if `rt_task_set_periodic()` has not previously been called for the calling task.
- -EINTR is returned if `rt_task_unblock()` has been called for the waiting task before the next periodic release point has been reached. In this case, the overrun counter is reset too.
- -ETIMEDOUT is returned if a timer overrun occurred, which indicates that a previous release point has been missed by the calling task. If *overruns_r* is valid, the count of pending overruns is copied to the pointed memory location.
- -EPERM is returned if this service was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel-based task
- User-space task (switches to primary mode)

Rescheduling: always, unless the current release point has already been reached. In the latter case, the current task immediately returns from this service without being delayed.

4.12.2.28 `int rt_task_yield (void)`

Manual round-robin.

Move the current task to the end of its priority group, so that the next equal-priority task in ready state is switched in.

Returns:

0 is returned upon success. Otherwise:

- -EPERM is returned if this service was called from a context which cannot sleep (e.g. interrupt, non-realtime or scheduler locked).

Environments:

This service can be called from:

- Kernel-based task
- User-space task

Rescheduling: always if a next equal-priority task is ready to run, otherwise, this service leads to a no-op.

4.13 Timer management services.

Collaboration diagram for Timer management services.:



4.13.1 Detailed Description

Timer-related services allow to control the Xenomai system timer which is used in all timed operations.

Files

- file [timer.c](#)

This file is part of the Xenomai project.

Functions

- SRTIME [rt_timer_ns2ticks](#) (SRTIME ns)
- SRTIME [rt_timer_ns2tsc](#) (SRTIME ns)
- SRTIME [rt_timer_ticks2ns](#) (SRTIME ticks)
 - Convert internal clock ticks to nanoseconds.*
- SRTIME [rt_timer_tsc2ns](#) (SRTIME ticks)
 - Convert local CPU clock ticks to nanoseconds.*
- int [rt_timer_inquire](#) (RT_TIMER_INFO *info)
 - Inquire about the timer.*
- RTIME [rt_timer_read](#) (void)
 - Return the current system time.*
- RTIME [rt_timer_tsc](#) (void)
 - Return the current TSC value.*
- void [rt_timer_spin](#) (RTIME ns)
- int [rt_timer_set_mode](#) (RTIME nstick)

4.13.2 Function Documentation

4.13.2.1 int [rt_timer_inquire](#) (RT_TIMER_INFO * info)

Inquire about the timer.

Return various information about the status of the system timer.

Parameters:

info The address of a structure the timer information will be written to.

Returns:

This service always returns 0.

The information block returns the period and the current system date. The period can have the following values:

- `TM_UNSET` is a special value indicating that the system timer is inactive. A call to `rt_timer_set_mode()` re-activates it.
- `TM_ONESHOT` is a special value indicating that the timer has been set up in oneshot mode.
- Any other period value indicates that the system timer is currently running in periodic mode; it is a count of nanoseconds representing the period of the timer, i.e. the duration of a periodic tick or "jiffy".

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.13.2.2 SRTIME `rt_timer_ns2ticks` (SRTIME *ns*)

Convert nanoseconds to internal clock ticks.

Convert a count of nanoseconds to internal clock ticks. This routine operates on signed nanosecond values.

Parameters:

ns The count of nanoseconds to convert.

Returns:

The corresponding value expressed in internal clock ticks.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.13.2.3 SRTIME `rt_timer_ns2tsc` (SRTIME *ns*)

Convert nanoseconds to local CPU clock ticks.

Convert a count of nanoseconds to local CPU clock ticks. This routine operates on signed nanosecond values.

Parameters:

ns The count of nanoseconds to convert.

Returns:

The corresponding value expressed in CPU clock ticks.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.13.2.4 RTIME `rt_timer_read` (void)

Return the current system time.

Return the current time maintained by the system timer.

Returns:

The current time expressed in clock ticks (see note).

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

Note:

This service is sensitive to the current operation mode of the system timer, as defined by the `CONFIG_XENO_OPT_TIMING_PERIOD` parameter. In periodic mode, clock ticks are interpreted as periodic jiffies. In oneshot mode, clock ticks are interpreted as nanoseconds.

4.13.2.5 `int rt_timer_set_mode (RTIME nstick)`

Set the system clock rate.

This routine switches to periodic timing mode and sets the clock tick rate, or resets the current timing mode to aperiodic/oneshot mode depending on the value of the *nstick* parameter. Since the Xenomai nucleus automatically starts the system timer according to the configured policy and period when a real-time skin is loaded (see `CONFIG_XENO_OPT_TIMING_PERIOD`), calling `rt_timer_set_mode()` is not required from applications unless the pre-defined mode and period need to be changed dynamically.

This service also sets the time unit which will be relevant when specifying time intervals to the services taking timeout or delays as input parameters. In periodic mode, clock ticks will represent periodic jiffies. In oneshot mode, clock ticks will represent nanoseconds.

Parameters:

nstick The timer period in nanoseconds. If this parameter is equal to the special `TM_ONESHOT` value, the timer is set to operate in oneshot-programmable mode. Other values are interpreted as the time between two consecutive clock ticks in periodic timing mode (i.e. $\text{clock HZ} = 1e9 / \text{nstick}$).

Returns:

0 is returned on success. Otherwise:

- `-ENODEV` is returned if the underlying architecture does not support the requested periodic timing. Aperiodic/oneshot timing is always supported.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- User-space task

Rescheduling: never.

4.13.2.6 `void rt_timer_spin (RTIME ns)`

Busy wait burning CPU cycles.

Enter a busy waiting loop for a count of nanoseconds. The precision of this service largely depends on the availability of a time stamp counter on the current CPU.

Since this service is usually called with interrupts enabled, the caller might be preempted by other real-time activities, therefore the actual delay might be longer than specified.

Parameters:

ns The time to wait expressed in nanoseconds.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.13.2.7 SRTIME `rt_timer_ticks2ns` (SRTIME *ticks*)

Convert internal clock ticks to nanoseconds.

Convert a count of internal clock ticks to nanoseconds. This routine operates on signed tick values.

Parameters:

ticks The count of internal clock ticks to convert.

Returns:

The corresponding value expressed in nanoseconds.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

4.13.2.8 RTIME `rt_timer_tsc` (void)

Return the current TSC value.

Return the value of the time stamp counter (TSC) maintained by the CPU of the underlying architecture.

Returns:

The current value of the TSC.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine

- Kernel-based task
- User-space task

Rescheduling: never.

4.13.2.9 SRTIME `rt_timer_tsc2ns` (SRTIME *ticks*)

Convert local CPU clock ticks to nanoseconds.

Convert a local CPU clock ticks to nanoseconds. This routine operates on signed tick values.

Parameters:

ticks The count of local CPU clock ticks to convert.

Returns:

The corresponding value expressed in nanoseconds.

Environments:

This service can be called from:

- Kernel module initialization/cleanup code
- Interrupt service routine
- Kernel-based task
- User-space task

Rescheduling: never.

Chapter 5

Xenomai Native skin API Data Structure Documentation

5.1 RT_TASK_INFO Struct Reference

5.1.1 Detailed Description

Structure containing task-information useful to users.

See also:

[rt_task_inquire\(\)](#)

Data Fields

- int [bprio](#)
Base priority.
- int [cprio](#)
Current priority.
- unsigned [status](#)
Task's status.
- RTIME [relpoint](#)
Time of next release.
- char [name](#) [XNOBJECT_NAME_LEN]
Symbolic name assigned at creation.

5.1.2 Field Documentation

5.1.2.1 `int RT_TASK_INFO::bprio`

Base priority.

5.1.2.2 `int RT_TASK_INFO::cprio`

Current priority.

May change through Priority Inheritance.

5.1.2.3 `unsigned RT_TASK_INFO::status`

Task's status.

See also:

[Task Status](#)

5.1.2.4 `RTIME RT_TASK_INFO::relpoint`

Time of next release.

5.1.2.5 `char RT_TASK_INFO::name[XNOBJECT_NAME_LEN]`

Symbolic name assigned at creation.

The documentation for this struct was generated from the following file:

- `include/native/task.h`

5.2 RT_TASK_MCB Struct Reference

5.2.1 Detailed Description

Structure used in passing messages between tasks.

See also:

[rt_task_send\(\)](#), [rt_task_reply\(\)](#), [rt_task_receive\(\)](#)

Data Fields

- `int flowid`
Flow identifier.
- `int opcode`
Operation code.
- `caddr_t data`
Message address.
- `size_t size`
Message size (bytes).

5.2.2 Field Documentation

5.2.2.1 `int RT_TASK_MCB::flowid`

Flow identifier.

5.2.2.2 `int RT_TASK_MCB::opcode`

Operation code.

5.2.2.3 `caddr_t RT_TASK_MCB::data`

Message address.

5.2.2.4 `size_t RT_TASK_MCB::size`

Message size (bytes).

The documentation for this struct was generated from the following file:

- `include/native/task.h`

Chapter 6

Xenomai Native skin API File Documentation

6.1 include/native/alarm.h File Reference

6.1.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for alarm.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_alarm_create` (`RT_ALARM *alarm`, `const char *name`)
- `int rt_alarm_wait` (`RT_ALARM *alarm`)
- `int rt_alarm_delete` (`RT_ALARM *alarm`)
- `int rt_alarm_start` (`RT_ALARM *alarm`, `RTIME value`, `RTIME interval`)
- `int rt_alarm_stop` (`RT_ALARM *alarm`)
- `int rt_alarm_inquire` (`RT_ALARM *alarm`, `RT_ALARM_INFO *info`)

6.2 include/native/cond.h File Reference

6.2.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for cond.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_cond_bind` (RT_COND *cond, const char *name, RTIME timeout)
- `static int rt_cond_unbind` (RT_COND *cond)
- `int rt_cond_create` (RT_COND *cond, const char *name)
- `int rt_cond_delete` (RT_COND *cond)
- `int rt_cond_signal` (RT_COND *cond)
- `int rt_cond_broadcast` (RT_COND *cond)
- `int rt_cond_wait` (RT_COND *cond, RT_MUTEX *mutex, RTIME timeout)
- `int rt_cond_inquire` (RT_COND *cond, RT_COND_INFO *info)

6.3 include/native/event.h File Reference

6.3.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for event.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_event_bind` (RT_EVENT *event, const char *name, RTIME timeout)
- `static int rt_event_unbind` (RT_EVENT *event)
- `int rt_event_create` (RT_EVENT *event, const char *name, unsigned long ivalue, int mode)
- `int rt_event_delete` (RT_EVENT *event)
- `int rt_event_signal` (RT_EVENT *event, unsigned long mask)
- `int rt_event_wait` (RT_EVENT *event, unsigned long mask, unsigned long *mask_r, int mode, RTIME timeout)
- `int rt_event_clear` (RT_EVENT *event, unsigned long mask, unsigned long *mask_r)
- `int rt_event_inquire` (RT_EVENT *event, RT_EVENT_INFO *info)

6.4 include/native/heap.h File Reference

6.4.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for heap.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_heap_bind` (RT_HEAP *heap, const char *name, RTIME timeout)
- `int rt_heap_unbind` (RT_HEAP *heap)
- `int rt_heap_create` (RT_HEAP *heap, const char *name, size_t heapsize, int mode)
Create a memory heap or a shared memory segment.
- `int rt_heap_delete` (RT_HEAP *heap)
- `int rt_heap_alloc` (RT_HEAP *heap, size_t size, RTIME timeout, void **blockp)
- `int rt_heap_free` (RT_HEAP *heap, void *block)
- `int rt_heap_inquire` (RT_HEAP *heap, RT_HEAP_INFO *info)

6.5 include/native/intr.h File Reference

6.5.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2005 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for intr.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_intr_bind` (RT_INTR *intr, const char *name, RTIME timeout)
- `static int rt_intr_unbind` (RT_INTR *intr)
- `int rt_intr_create` (RT_INTR *intr, const char *name, unsigned irq, int mode)

Create an interrupt object from user-space.

- `int rt_intr_wait` (RT_INTR *intr, RTIME timeout)
- `int rt_intr_delete` (RT_INTR *intr)
- `int rt_intr_enable` (RT_INTR *intr)

Enable an interrupt object.

- int [rt_intr_disable](#) (RT_INTR *intr)
Disable an interrupt object.
- int [rt_intr_inquire](#) (RT_INTR *intr, RT_INTR_INFO *info)

6.6 include/native/misc.h File Reference

6.6.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2005 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for misc.h:



6.7 include/native/mutex.h File Reference

6.7.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for mutex.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_mutex_bind (RT_MUTEX *mutex, const char *name, RTIME timeout)`
- `static int rt_mutex_unbind (RT_MUTEX *mutex)`
- `int rt_mutex_create (RT_MUTEX *mutex, const char *name)`
- `int rt_mutex_delete (RT_MUTEX *mutex)`
- `int rt_mutex_acquire (RT_MUTEX *mutex, RTIME timeout)`
- `int rt_mutex_release (RT_MUTEX *mutex)`
- `int rt_mutex_inquire (RT_MUTEX *mutex, RT_MUTEX_INFO *info)`

6.8 include/native/pipe.h File Reference

6.8.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for pipe.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_pipe_create` (RT_PIPE *pipe, const char *name, int minor, size_t poolsize)
- `int rt_pipe_delete` (RT_PIPE *pipe)
- `ssize_t rt_pipe_read` (RT_PIPE *pipe, void *buf, size_t size, RTIME timeout)
- `ssize_t rt_pipe_write` (RT_PIPE *pipe, const void *buf, size_t size, int mode)
- `ssize_t rt_pipe_stream` (RT_PIPE *pipe, const void *buf, size_t size)

6.9 include/native/queue.h File Reference

6.9.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for queue.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_queue_bind` (`RT_QUEUE *q`, `const char *name`, `RTIME timeout`)
- `int rt_queue_unbind` (`RT_QUEUE *q`)
- `int rt_queue_create` (`RT_QUEUE *q`, `const char *name`, `size_t poolsize`, `size_t qlimit`, `int mode`)
- `int rt_queue_delete` (`RT_QUEUE *q`)
- `void * rt_queue_alloc` (`RT_QUEUE *q`, `size_t size`)
- `int rt_queue_free` (`RT_QUEUE *q`, `void *buf`)
- `int rt_queue_send` (`RT_QUEUE *q`, `void *buf`, `size_t size`, `int mode`)
- `int rt_queue_write` (`RT_QUEUE *q`, `const void *buf`, `size_t size`, `int mode`)
- `ssize_t rt_queue_receive` (`RT_QUEUE *q`, `void **bufp`, `RTIME timeout`)

- [ssize_t rt_queue_read](#) (RT_QUEUE *q, void *bufp, size_t size, RTIME timeout)
- [int rt_queue_inquire](#) (RT_QUEUE *q, RT_QUEUE_INFO *info)

6.10 include/native/sem.h File Reference

6.10.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for sem.h:



This graph shows which files directly or indirectly include this file:



Functions

- `int rt_sem_bind` (RT_SEM *sem, const char *name, RTIME timeout)
- `static int rt_sem_unbind` (RT_SEM *sem)
- `int rt_sem_create` (RT_SEM *sem, const char *name, unsigned long icount, int mode)
- `int rt_sem_delete` (RT_SEM *sem)
- `int rt_sem_p` (RT_SEM *sem, RTIME timeout)
- `int rt_sem_v` (RT_SEM *sem)
- `int rt_sem_broadcast` (RT_SEM *sem)
- `int rt_sem_inquire` (RT_SEM *sem, RT_SEM_INFO *info)

6.11 include/native/task.h File Reference

6.11.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for task.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- struct [RT_TASK_INFO](#)
Structure containing task-information useful to users.
- struct [RT_TASK_MCB](#)
Structure used in passing messages between tasks.

Defines

- #define [T_BLOCKED](#) XNPEND

See *XNPEND*.

- #define [T_DELAYED](#) XNDELAY
See *XNDELAY*.
- #define [T_READY](#) XNREADY
See *XNREADY*.
- #define [T_DORMANT](#) XNDORMANT
See *XNDORMANT*.
- #define [T_STARTED](#) XNSTARTED
See *XNSTARTED*.
- #define [T_BOOST](#) XNBOOST
See *XNBOOST*.
- #define [T_LOCK](#) XNLOCK
See *XNLOCK*.
- #define [T_RRB](#) XNRRB
See *XNRRB*.
- #define [T_NOSIG](#) XNASDI
See *XNASDI*.
- #define [T_SHIELD](#) XNSHIELD
See *XNSHIELD*.
- #define [T_WARNSW](#) XNTRAPSW
See *XNTRAPSW*.
- #define [T_RPIOFF](#) XNRPIOFF
See *XNRPIOFF*.

Functions

- int [rt_task_shadow](#) (RT_TASK *task, const char *name, int prio, int mode)
- int [rt_task_bind](#) (RT_TASK *task, const char *name, RTIME timeout)
- static int [rt_task_unbind](#) (RT_TASK *task)
- int [rt_task_join](#) (RT_TASK *task)
- int [rt_task_create](#) (RT_TASK *task, const char *name, int stksize, int prio, int mode)
- int [rt_task_start](#) (RT_TASK *task, void(*fun)(void *cookie), void *cookie)
- int [rt_task_suspend](#) (RT_TASK *task)
- int [rt_task_resume](#) (RT_TASK *task)
- int [rt_task_delete](#) (RT_TASK *task)
- int [rt_task_yield](#) (void)
- int [rt_task_set_periodic](#) (RT_TASK *task, RTIME idate, RTIME period)
- int [rt_task_wait_period](#) (unsigned long *overruns_r)

- int `rt_task_set_priority` (RT_TASK *task, int prio)
- int `rt_task_sleep` (RTIME delay)
- int `rt_task_sleep_until` (RTIME date)
- int `rt_task_unblock` (RT_TASK *task)
- int `rt_task_inquire` (RT_TASK *task, RT_TASK_INFO *info)
- int `rt_task_notify` (RT_TASK *task, rt_sigset_t signals)
- int `rt_task_set_mode` (int clrmask, int setmask, int *mode_r)
- RT_TASK * `rt_task_self` (void)
- int `rt_task_slice` (RT_TASK *task, RTIME quantum)
- ssize_t `rt_task_send` (RT_TASK *task, RT_TASK_MCB *mcb_s, RT_TASK_MCB *mcb_r, RTIME timeout)
- int `rt_task_receive` (RT_TASK_MCB *mcb_r, RTIME timeout)
- int `rt_task_reply` (int flowid, RT_TASK_MCB *mcb_s)
- static int `rt_task_spawn` (RT_TASK *task, const char *name, int stksize, int prio, int mode, void(*entry)(void *cookie), void *cookie)

6.12 include/native/timer.h File Reference

6.12.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for timer.h:



This graph shows which files directly or indirectly include this file:



Functions

- SRTIME [rt_timer_ns2ticks](#) (SRTIME ns)
- SRTIME [rt_timer_ticks2ns](#) (SRTIME ticks)
Convert internal clock ticks to nanoseconds.
- SRTIME [rt_timer_ns2tsc](#) (SRTIME ns)
- SRTIME [rt_timer_tsc2ns](#) (SRTIME ticks)
Convert local CPU clock ticks to nanoseconds.
- int [rt_timer_inquire](#) (RT_TIMER_INFO *info)
Inquire about the timer.

- RTIME [rt_timer_read](#) (void)
Return the current system time.
- RTIME [rt_timer_tsc](#) (void)
Return the current TSC value.
- void [rt_timer_spin](#) (RTIME ns)
- int [rt_timer_set_mode](#) (RTIME nstick)

6.13 include/native/types.h File Reference

6.13.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.


This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for types.h:



This graph shows which files directly or indirectly include this file:



6.14 ksrc/skins/native/module.c File Reference

6.14.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for module.c:



6.15 ksrc/skins/native/syscall.c File Reference

6.15.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for syscall.c:



6.16 ksrc/skins/native/alarm.c File Reference

6.16.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for alarm.c:



Functions

- `int rt_alarm_create` (RT_ALARM *alarm, const char *name, rt_alarm_t handler, void *cookie)
- `int rt_alarm_delete` (RT_ALARM *alarm)
- `int rt_alarm_start` (RT_ALARM *alarm, RTIME value, RTIME interval)
- `int rt_alarm_stop` (RT_ALARM *alarm)
- `int rt_alarm_inquire` (RT_ALARM *alarm, RT_ALARM_INFO *info)

6.17 ksrc/skins/native/cond.c File Reference

6.17.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for cond.c:



Functions

- `int rt_cond_create` (`RT_COND *cond`, `const char *name`)
- `int rt_cond_delete` (`RT_COND *cond`)
- `int rt_cond_signal` (`RT_COND *cond`)
- `int rt_cond_broadcast` (`RT_COND *cond`)
- `int rt_cond_wait` (`RT_COND *cond`, `RT_MUTEX *mutex`, `RTIME timeout`)
- `int rt_cond_inquire` (`RT_COND *cond`, `RT_COND_INFO *info`)

6.18 ksrc/skins/native/event.c File Reference

6.18.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for event.c:



Functions

- `int rt_event_create` (RT_EVENT *event, const char *name, unsigned long ivalue, int mode)
- `int rt_event_delete` (RT_EVENT *event)
- `int rt_event_signal` (RT_EVENT *event, unsigned long mask)
- `int rt_event_wait` (RT_EVENT *event, unsigned long mask, unsigned long *mask_r, int mode, RTIME timeout)
- `int rt_event_clear` (RT_EVENT *event, unsigned long mask, unsigned long *mask_r)
- `int rt_event_inquire` (RT_EVENT *event, RT_EVENT_INFO *info)

6.19 ksrc/skins/native/heap.c File Reference

6.19.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for heap.c:



Functions

- `int rt_heap_create` (`RT_HEAP *heap`, `const char *name`, `size_t heapsize`, `int mode`)
Create a memory heap or a shared memory segment.
- `int rt_heap_delete` (`RT_HEAP *heap`)
- `int rt_heap_alloc` (`RT_HEAP *heap`, `size_t size`, `RTIME timeout`, `void **blockp`)
- `int rt_heap_free` (`RT_HEAP *heap`, `void *block`)
- `int rt_heap_inquire` (`RT_HEAP *heap`, `RT_HEAP_INFO *info`)

6.20 ksrc/skins/native/intr.c File Reference

6.20.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2005 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for intr.c:



Functions

- `int rt_intr_create` (RT_INTR *intr, const char *name, unsigned irq, rt_isr_t isr, rt_iack_t iack, int mode)
Create an interrupt object from kernel space.
- `int rt_intr_delete` (RT_INTR *intr)
- `int rt_intr_enable` (RT_INTR *intr)
Enable an interrupt object.
- `int rt_intr_disable` (RT_INTR *intr)
Disable an interrupt object.
- `int rt_intr_inquire` (RT_INTR *intr, RT_INTR_INFO *info)

6.21 ksrc/skins/native/mutex.c File Reference

6.21.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for mutex.c:



Functions

- `int rt_mutex_create` (RT_MUTEX *mutex, const char *name)
- `int rt_mutex_delete` (RT_MUTEX *mutex)
- `int rt_mutex_acquire` (RT_MUTEX *mutex, RTIME timeout)
- `int rt_mutex_release` (RT_MUTEX *mutex)
- `int rt_mutex_inquire` (RT_MUTEX *mutex, RT_MUTEX_INFO *info)

6.22 ksrc/skins/native/pipe.c File Reference

6.22.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for pipe.c:



Functions

- `int rt_pipe_create` (`RT_PIPE *pipe`, `const char *name`, `int minor`, `size_t poolsize`)
- `int rt_pipe_delete` (`RT_PIPE *pipe`)
- `ssize_t rt_pipe_receive` (`RT_PIPE *pipe`, `RT_PIPE_MSG **msgp`, `RTIME timeout`)
- `ssize_t rt_pipe_read` (`RT_PIPE *pipe`, `void *buf`, `size_t size`, `RTIME timeout`)
- `ssize_t rt_pipe_send` (`RT_PIPE *pipe`, `RT_PIPE_MSG *msg`, `size_t size`, `int mode`)
- `ssize_t rt_pipe_write` (`RT_PIPE *pipe`, `const void *buf`, `size_t size`, `int mode`)
- `ssize_t rt_pipe_stream` (`RT_PIPE *pipe`, `const void *buf`, `size_t size`)
- `ssize_t rt_pipe_flush` (`RT_PIPE *pipe`)
- `RT_PIPE_MSG * rt_pipe_alloc` (`RT_PIPE *pipe`, `size_t size`)
- `int rt_pipe_free` (`RT_PIPE *pipe`, `RT_PIPE_MSG *msg`)

6.23 ksrc/skins/native/queue.c File Reference

6.23.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for queue.c:



Functions

- [int rt_queue_create](#) (RT_QUEUE *q, const char *name, size_t poolsize, size_t qlimit, int mode)
- [int rt_queue_delete](#) (RT_QUEUE *q)
- [void * rt_queue_alloc](#) (RT_QUEUE *q, size_t size)
- [int rt_queue_free](#) (RT_QUEUE *q, void *buf)
- [int rt_queue_send](#) (RT_QUEUE *q, void *mbuf, size_t size, int mode)
- [int rt_queue_write](#) (RT_QUEUE *q, const void *buf, size_t size, int mode)
- [ssize_t rt_queue_receive](#) (RT_QUEUE *q, void **bufp, RTIME timeout)
- [ssize_t rt_queue_read](#) (RT_QUEUE *q, void *buf, size_t size, RTIME timeout)
- [int rt_queue_inquire](#) (RT_QUEUE *q, RT_QUEUE_INFO *info)

6.24 ksrc/skins/native/sem.c File Reference

6.24.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for sem.c:



Functions

- `int rt_sem_create` (RT_SEM *sem, const char *name, unsigned long icount, int mode)
- `int rt_sem_delete` (RT_SEM *sem)
- `int rt_sem_p` (RT_SEM *sem, RTIME timeout)
- `int rt_sem_v` (RT_SEM *sem)
- `int rt_sem_broadcast` (RT_SEM *sem)
- `int rt_sem_inquire` (RT_SEM *sem, RT_SEM_INFO *info)

6.25 ksrc/skins/native/task.c File Reference

6.25.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for task.c:



Functions

- `int rt_task_create` (RT_TASK *task, const char *name, int stksize, int prio, int mode)
- `int rt_task_start` (RT_TASK *task, void(*entry)(void *cookie), void *cookie)
- `int rt_task_suspend` (RT_TASK *task)
- `int rt_task_resume` (RT_TASK *task)
- `int rt_task_delete` (RT_TASK *task)
- `int rt_task_yield` (void)
- `int rt_task_set_periodic` (RT_TASK *task, RTIME idate, RTIME period)
- `int rt_task_wait_period` (unsigned long *overruns_r)
- `int rt_task_set_priority` (RT_TASK *task, int prio)
- `int rt_task_sleep` (RTIME delay)
- `int rt_task_sleep_until` (RTIME date)
- `int rt_task_unblock` (RT_TASK *task)
- `int rt_task_inquire` (RT_TASK *task, RT_TASK_INFO *info)

- int [rt_task_add_hook](#) (int type, void(*routine)(void *cookie))
- int [rt_task_remove_hook](#) (int type, void(*routine)(void *cookie))
- int [rt_task_catch](#) (void(*handler)(rt_sigset_t))
- int [rt_task_notify](#) (RT_TASK *task, rt_sigset_t signals)
- int [rt_task_set_mode](#) (int clrmask, int setmask, int *mode_r)
- RT_TASK * [rt_task_self](#) (void)
- int [rt_task_slice](#) (RT_TASK *task, RTIME quantum)
- ssize_t [rt_task_send](#) (RT_TASK *task, [RT_TASK_MCB](#) *mcb_s, [RT_TASK_MCB](#) *mcb_r, RTIME timeout)
- int [rt_task_receive](#) ([RT_TASK_MCB](#) *mcb_r, RTIME timeout)
- int [rt_task_reply](#) (int flowid, [RT_TASK_MCB](#) *mcb_s)

6.26 ksrc/skins/native/timer.c File Reference

6.26.1 Detailed Description

This file is part of the Xenomai project.

Note:


Copyright (C) 2004 Philippe Gerum <rpm@xenomai.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Include dependency graph for timer.c:



Functions

- SRTIME [rt_timer_ns2ticks](#) (SRTIME ns)
- SRTIME [rt_timer_ns2tsc](#) (SRTIME ns)
- SRTIME [rt_timer_ticks2ns](#) (SRTIME ticks)
 - Convert internal clock ticks to nanoseconds.*
- SRTIME [rt_timer_tsc2ns](#) (SRTIME ticks)
 - Convert local CPU clock ticks to nanoseconds.*
- int [rt_timer_inquire](#) (RT_TIMER_INFO *info)
 - Inquire about the timer.*
- RTIME [rt_timer_read](#) (void)
 - Return the current system time.*
- RTIME [rt_timer_tsc](#) (void)

Return the current TSC value.

- void [rt_timer_spin](#) (RTIME ns)
- int [rt_timer_set_mode](#) (RTIME nstick)

Index

- alarm
 - [rt_alarm_create](#), [9](#), [10](#)
 - [rt_alarm_delete](#), [11](#)
 - [rt_alarm_inquire](#), [11](#)
 - [rt_alarm_start](#), [12](#)
 - [rt_alarm_stop](#), [13](#)
 - [rt_alarm_wait](#), [14](#)
- Alarm services., [9](#)
- bprio
 - [RT_TASK_INFO](#), [114](#)
- cond
 - [rt_cond_bind](#), [15](#)
 - [rt_cond_broadcast](#), [16](#)
 - [rt_cond_create](#), [17](#)
 - [rt_cond_delete](#), [17](#)
 - [rt_cond_inquire](#), [18](#)
 - [rt_cond_signal](#), [19](#)
 - [rt_cond_unbind](#), [19](#)
 - [rt_cond_wait](#), [20](#)
- Condition variable services., [15](#)
- Counting semaphore services., [74](#)
- cprio
 - [RT_TASK_INFO](#), [114](#)
- data
 - [RT_TASK_MCB](#), [115](#)
- event
 - [rt_event_bind](#), [22](#)
 - [rt_event_clear](#), [23](#)
 - [rt_event_create](#), [24](#)
 - [rt_event_delete](#), [25](#)
 - [rt_event_inquire](#), [25](#)
 - [rt_event_signal](#), [26](#)
 - [rt_event_unbind](#), [27](#)
 - [rt_event_wait](#), [27](#)
- Event flag group services., [22](#)
- flowid
 - [RT_TASK_MCB](#), [115](#)
- [include/native/alarm.h](#), [117](#)
- [include/native/cond.h](#), [119](#)
- [include/native/event.h](#), [120](#)
- [include/native/heap.h](#), [121](#)
- [include/native/intr.h](#), [122](#)
- [include/native/misc.h](#), [124](#)
- [include/native/mutex.h](#), [125](#)
- [include/native/pipe.h](#), [126](#)
- [include/native/queue.h](#), [127](#)
- [include/native/sem.h](#), [129](#)
- [include/native/task.h](#), [130](#)
- [include/native/timer.h](#), [133](#)
- [include/native/types.h](#), [135](#)
- interrupt
 - [rt_intr_bind](#), [36](#)
 - [rt_intr_create](#), [37](#), [38](#)
 - [rt_intr_delete](#), [40](#)
 - [rt_intr_disable](#), [41](#)
 - [rt_intr_enable](#), [41](#)
 - [rt_intr_inquire](#), [42](#)
 - [rt_intr_unbind](#), [43](#)
 - [rt_intr_wait](#), [43](#)
- Interrupt management services., [36](#)
- [ksrc/skins/native/alarm.c](#), [138](#)
- [ksrc/skins/native/cond.c](#), [139](#)
- [ksrc/skins/native/event.c](#), [140](#)
- [ksrc/skins/native/heap.c](#), [141](#)
- [ksrc/skins/native/intr.c](#), [142](#)
- [ksrc/skins/native/module.c](#), [136](#)
- [ksrc/skins/native/mutex.c](#), [143](#)
- [ksrc/skins/native/pipe.c](#), [144](#)
- [ksrc/skins/native/queue.c](#), [145](#)
- [ksrc/skins/native/sem.c](#), [146](#)
- [ksrc/skins/native/syscall.c](#), [137](#)
- [ksrc/skins/native/task.c](#), [147](#)
- [ksrc/skins/native/timer.c](#), [149](#)
- Memory heap services., [29](#)
- Message pipe services., [52](#)
- Message queue services., [63](#)
- mutex
 - [rt_mutex_acquire](#), [46](#)
 - [rt_mutex_bind](#), [47](#)
 - [rt_mutex_create](#), [48](#)
 - [rt_mutex_delete](#), [49](#)
 - [rt_mutex_inquire](#), [50](#)
 - [rt_mutex_release](#), [50](#)

- rt_mutex_unbind, 51
- Mutex services., 46
- name
 - RT_TASK_INFO, 114
- Native Xenomai API., 45
- native_heap
 - rt_heap_alloc, 29
 - rt_heap_bind, 31
 - rt_heap_create, 32
 - rt_heap_delete, 33
 - rt_heap_free, 34
 - rt_heap_inquire, 34
 - rt_heap_unbind, 35
- native_queue
 - rt_queue_alloc, 63
 - rt_queue_bind, 64
 - rt_queue_create, 65
 - rt_queue_delete, 66
 - rt_queue_free, 67
 - rt_queue_inquire, 67
 - rt_queue_read, 68
 - rt_queue_receive, 69
 - rt_queue_send, 70
 - rt_queue_unbind, 71
 - rt_queue_write, 72
- native_timer
 - rt_timer_inquire, 107
 - rt_timer_ns2ticks, 108
 - rt_timer_ns2tsc, 108
 - rt_timer_read, 109
 - rt_timer_set_mode, 109
 - rt_timer_spin, 110
 - rt_timer_ticks2ns, 111
 - rt_timer_tsc, 111
 - rt_timer_tsc2ns, 112
- opcode
 - RT_TASK_MCB, 115
- pipe
 - rt_pipe_alloc, 52
 - rt_pipe_create, 53
 - rt_pipe_delete, 54
 - rt_pipe_flush, 55
 - rt_pipe_free, 55
 - rt_pipe_read, 56
 - rt_pipe_receive, 57
 - rt_pipe_send, 59
 - rt_pipe_stream, 60
 - rt_pipe_write, 61
- relpoint
 - RT_TASK_INFO, 114
- rt_alarm_create
 - alarm, 9, 10
- rt_alarm_delete
 - alarm, 11
- rt_alarm_inquire
 - alarm, 11
- rt_alarm_start
 - alarm, 12
- rt_alarm_stop
 - alarm, 13
- rt_alarm_wait
 - alarm, 14
- rt_cond_bind
 - cond, 15
- rt_cond_broadcast
 - cond, 16
- rt_cond_create
 - cond, 17
- rt_cond_delete
 - cond, 17
- rt_cond_inquire
 - cond, 18
- rt_cond_signal
 - cond, 19
- rt_cond_unbind
 - cond, 19
- rt_cond_wait
 - cond, 20
- rt_event_bind
 - event, 22
- rt_event_clear
 - event, 23
- rt_event_create
 - event, 24
- rt_event_delete
 - event, 25
- rt_event_inquire
 - event, 25
- rt_event_signal
 - event, 26
- rt_event_unbind
 - event, 27
- rt_event_wait
 - event, 27
- rt_heap_alloc
 - native_heap, 29
- rt_heap_bind
 - native_heap, 31
- rt_heap_create
 - native_heap, 32
- rt_heap_delete
 - native_heap, 33
- rt_heap_free
 - native_heap, 34

- rt_heap_inquire
 - native_heap, [34](#)
- rt_heap_unbind
 - native_heap, [35](#)
- rt_intr_bind
 - interrupt, [36](#)
- rt_intr_create
 - interrupt, [37, 38](#)
- rt_intr_delete
 - interrupt, [40](#)
- rt_intr_disable
 - interrupt, [41](#)
- rt_intr_enable
 - interrupt, [41](#)
- rt_intr_inquire
 - interrupt, [42](#)
- rt_intr_unbind
 - interrupt, [43](#)
- rt_intr_wait
 - interrupt, [43](#)
- rt_mutex_acquire
 - mutex, [46](#)
- rt_mutex_bind
 - mutex, [47](#)
- rt_mutex_create
 - mutex, [48](#)
- rt_mutex_delete
 - mutex, [49](#)
- rt_mutex_inquire
 - mutex, [50](#)
- rt_mutex_release
 - mutex, [50](#)
- rt_mutex_unbind
 - mutex, [51](#)
- rt_pipe_alloc
 - pipe, [52](#)
- rt_pipe_create
 - pipe, [53](#)
- rt_pipe_delete
 - pipe, [54](#)
- rt_pipe_flush
 - pipe, [55](#)
- rt_pipe_free
 - pipe, [55](#)
- rt_pipe_read
 - pipe, [56](#)
- rt_pipe_receive
 - pipe, [57](#)
- rt_pipe_send
 - pipe, [59](#)
- rt_pipe_stream
 - pipe, [60](#)
- rt_pipe_write
 - pipe, [61](#)
- rt_queue_alloc
 - native_queue, [63](#)
- rt_queue_bind
 - native_queue, [64](#)
- rt_queue_create
 - native_queue, [65](#)
- rt_queue_delete
 - native_queue, [66](#)
- rt_queue_free
 - native_queue, [67](#)
- rt_queue_inquire
 - native_queue, [67](#)
- rt_queue_read
 - native_queue, [68](#)
- rt_queue_receive
 - native_queue, [69](#)
- rt_queue_send
 - native_queue, [70](#)
- rt_queue_unbind
 - native_queue, [71](#)
- rt_queue_write
 - native_queue, [72](#)
- rt_sem_bind
 - semaphore, [74](#)
- rt_sem_broadcast
 - semaphore, [75](#)
- rt_sem_create
 - semaphore, [76](#)
- rt_sem_delete
 - semaphore, [77](#)
- rt_sem_inquire
 - semaphore, [77](#)
- rt_sem_p
 - semaphore, [78](#)
- rt_sem_unbind
 - semaphore, [79](#)
- rt_sem_v
 - semaphore, [79](#)
- rt_task_add_hook
 - task, [82](#)
- rt_task_bind
 - task, [83](#)
- rt_task_catch
 - task, [84](#)
- rt_task_create
 - task, [84](#)
- rt_task_delete
 - task, [85](#)
- RT_TASK_INFO, [113](#)
 - bprio, [114](#)
 - cprio, [114](#)
 - name, [114](#)
 - relpoint, [114](#)
 - status, [114](#)

- rt_task_inquire
 - task, 86
- rt_task_join
 - task, 87
- RT_TASK_MCB, 115
 - data, 115
 - flowid, 115
 - opcode, 115
 - size, 115
- rt_task_notify
 - task, 87
- rt_task_receive
 - task, 88
- rt_task_remove_hook
 - task, 90
- rt_task_reply
 - task, 90
- rt_task_resume
 - task, 91
- rt_task_self
 - task, 92
- rt_task_send
 - task, 92
- rt_task_set_mode
 - task, 94
- rt_task_set_periodic
 - task, 96
- rt_task_set_priority
 - task, 97
- rt_task_shadow
 - task, 98
- rt_task_sleep
 - task, 99
- rt_task_sleep_until
 - task, 99
- rt_task_slice
 - task, 100
- rt_task_spawn
 - task, 101
- rt_task_start
 - task, 102
- rt_task_suspend
 - task, 103
- rt_task_unbind
 - task, 104
- rt_task_unblock
 - task, 104
- rt_task_wait_period
 - task, 105
- rt_task_yield
 - task, 105
- rt_timer_inquire
 - native_timer, 107
- rt_timer_ns2ticks
 - native_timer, 108
- rt_timer_ns2tsc
 - native_timer, 108
- rt_timer_read
 - native_timer, 109
- rt_timer_set_mode
 - native_timer, 109
- rt_timer_spin
 - native_timer, 110
- rt_timer_ticks2ns
 - native_timer, 111
- rt_timer_tsc
 - native_timer, 111
- rt_timer_tsc2ns
 - native_timer, 112
- semaphore
 - rt_sem_bind, 74
 - rt_sem_broadcast, 75
 - rt_sem_create, 76
 - rt_sem_delete, 77
 - rt_sem_inquire, 77
 - rt_sem_p, 78
 - rt_sem_unbind, 79
 - rt_sem_v, 79
- size
 - RT_TASK_MCB, 115
- status
 - RT_TASK_INFO, 114
- task
 - rt_task_add_hook, 82
 - rt_task_bind, 83
 - rt_task_catch, 84
 - rt_task_create, 84
 - rt_task_delete, 85
 - rt_task_inquire, 86
 - rt_task_join, 87
 - rt_task_notify, 87
 - rt_task_receive, 88
 - rt_task_remove_hook, 90
 - rt_task_reply, 90
 - rt_task_resume, 91
 - rt_task_self, 92
 - rt_task_send, 92
 - rt_task_set_mode, 94
 - rt_task_set_periodic, 96
 - rt_task_set_priority, 97
 - rt_task_shadow, 98
 - rt_task_sleep, 99
 - rt_task_sleep_until, 99
 - rt_task_slice, 100
 - rt_task_spawn, 101
 - rt_task_start, 102

-
- rt_task_suspend, [103](#)
 - rt_task_unbind, [104](#)
 - rt_task_unblock, [104](#)
 - rt_task_wait_period, [105](#)
 - rt_task_yield, [105](#)
 - Task management services., [81](#)
 - Task Status, [7](#)
 - Timer management services., [107](#)